


Compliance with the current version of Kärcher standard KN 050.032 Constituent substances (ban of lead, cadmium, etc.) must be guaranteed. Standard date format according to ISO 8601 (YYYY-MM-DD). The reproduction, distribution and utilization of this document as well as the communication of its contents to others without explicit authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. Copyright © Alfred Kärcher GmbH & Co. KG

4	3	2	1
 KÄRCHER Winnenden		Benennung / description HD 16/15-4 Cage Plus *EU-I HD 16/15-4 Cage Plus *EU-I	
		Material-Nr. / material no. 1.367-100.0	

IMPORTANT NOTE
 Data is intended for Kärcher Service only
 and must not be passed on to unauthorised third parties!

Supply voltage / phases	V / Ph	400/3
Frequency	Hz	50
Connection power max.	kW	9,5
Electric motor speed	rpm	1400
Feed pressure water	MPa	0,2-0,4
High pressure nozzle (US-gpm at 40 psi)	US-gpm	25100
Flow rate, full load Pressure water	I/h	>1520
Flow rate, full load Suction water	I/h	—
Flow rate, partial load	I/h	750-900

		document		number	type	version	status	sheet	of
		Technical specificatio		5446204	TDA	01	FR	1	1
Datum date	Gezeichnet drawn by	Geprüft checked by	Normgeprüft std. checked by	Änderung / Engineering change			Ersatz für / replaces		
2015-03-12	AW03274	-----	-----	index	Anzahl / count	number	Datum / date	index	
4	3	2	1						

F
E
D
C
B
A