

# Vacuum sweepers walk-behind KSM 750 B Honda



#### Overview

Vacuum sweeper with robust petrol engine for outdoor use. Height-adjustable roller brush, handy mobile waste container. Dust created during sweeping is suctioned in and retained by a large filter. Mechanical filter shaker.

Order no. 1.049-144.0

#### Standard accessories

Vacuum, Outdoor applications, Indoor applications, Operating hour meter, Travel drive, forward, Mobile container, Bulk waste flap, Container capacity 40l, Roller brush, tunable, Fold-down push handle, Patented filter shaker system, Suction fan cut-out, Side brush, liftable/adjustable

#### **Technical data**

| Drive rating                    | 3.3 kW |
|---------------------------------|--------|
| Max. Area performance m²/h      | 2850   |
| Working width mm                | 550    |
| Working width (2) mm            | -      |
| Working width with 1 side brush | 710    |
| mm                              |        |
| Working width with 2 side       | -      |
| brushes mm                      |        |
| Hill climbing ability %         | 18     |
| Operating speed km/h            | 4      |
| Filter area m²                  | 2,1    |
| Weight kg                       | 75     |
|                                 |        |

#### **Description**

The KSM 750 B is a petrol-powered, walk-behind, self-propelled vacuum sweeper. The unit operates on the overthrow principle which allows the waste container to be filled almost to 100% of its capacity. A large-area fine dust filter with manual filter shaker ensures dust-free sweeping.

#### Drive:

HONDA four-stroke petrol engine Infinitely variable forward travel speed 0-4 km/h Ergonomically shaped handle for outstanding operator convenience Parking brake acts on front caster.



# Vacuum sweepers walk-behind

## KSM 750 B Honda



•••

Sweeping/vacuum system:

Retractable right side brush sweeps dust and dirt out of corners, and other awkward areas, into the path of the main roller brush. The adjustable roller brush collects the sweepings and conveys them into the large-capacity waste container. Fine dust is extracted by the fan and retained by the preseparator and filter. Mechanical shaker permits fast and convenient cleaning of filter. Suction can be switched off to protect filter while sweeping wet surfaces.

Waste container:

Mobile waste container is made of corrosion-free, high impact plastics and easily removed from the rear of the machine.

#### **Application**

The petrol version of the KSM 750 is suitable for dust-free sweeping of outdoor areas. Robust drive allows sweeping on gradients up to 18 %.

The KSM 750 B is recommended for professional applications. A single tankful (working time of about 4 hours) is sufficient to sweep areas of between 6,000 sq.m and 9,500 sq.m (50 - 80 % of theoretical sweeping capacity).

#### Features & Benefits

2.1 m² surface flat pleated filters and manually operated filter cleaning device. simple filter change. Separation-grade over 99.5%. efficient filtration.

4-stroke engine with primer starter pull cord, stop button in control panel Easy manual start and stop

Chassis from impact resistant plastic with bumper for side brush. Robust and longlife design. Protection of side brush against damage.

Collapsing handle.

Easy to transport and store.

Friction drive activated via hand lever.

Infinitely variable speed 0-4 km/h.

Incorporates vacuum for fine dust via radial fan.

Excellent sweeping performance. prevention of fine dust.

Operating hour meter.

Controll for maintenace.



# Vacuum sweepers walk-behind

#### KSM 750 B Honda

**...** 

Overthrow principle.

efficient filling of waste container.

safety switch under hood engine stops automatically if hood is opened

Side brush adjustable/ liftable via hand lever. simple operation, fulfils applications requirements.

Waste container with handle and rollers. easy to handle for debris disposal.

#### **Flachfaltenfilter**

#### Flachfaltenfilter

Plastic filter, moisture-proof, washable, saves maintenance costs Order no. 5.731-585.0



#### **Flusenfilter**

#### Fluff filter for carpet sweeping

For carpet sweeping. Stops carpet fibres from blocking filter Order no. 2.638-851.0



#### Main roller brush high/low

#### Main roller brush high/low KSM 750

For improved performance in dips and hollows, e.g. grooves or joints L= 550 mm Order no. 6.906-254.0



#### Main roller brush, antistatic

#### Main roller brush, anti-static KSM 750

For sweeping carpets, prevents electrostatic charging L= 550 mm
Order no. 6.906-026.0





# Vacuum sweepers walk-behind

### KSM 750 B Honda

#### Main roller brush, hard

#### Main roller brush, hard KSM 750

Removes stubborn dirt in outdoor areas, moisture-proof L= 550 mm Order no. 6.905-868.0



#### Main roller brush, soft/natural

#### Main roller brush, soft/natural KSM 750

With natural bristles, specially for sweeping fine dust on smooth indoor floors, not moisture-proof, not for abrasive floors
L= 550 mm



Order no. 6.905-870.0

#### Side brush, hard

#### Side brush, hard KSM 750

Removes stubborn dirt in outdoor areas, moisture-proof, mildly abrasive  $\emptyset$  390 mm

Order no. 6.951-164.0



#### Standard main roller brushes

#### Standard main brush KSM 750

Moisture-proof universal bristles, long life, suitable for all surfaces L= 550 mm
Order no. 6.905-587.0



#### Standard side brushes

#### Standard side brush KSM 750

Moisture-proof universal bristles, long life, suitable for all surfaces  $\emptyset$  290 mm

Order no. 6.951-073.0

