

Compliance with the current version of Kärcher standard KN 050.032 Constituent substances (ban of lead, cadmium, etc.) must be guaranteed. Standard date format according to ISO 8601 (YYYY-MM-DD).
 The reproduction, distribution and utilization of this document as well as the communication of its contents to others without explicit authorization is prohibited. Offenders will be held liable for the payment of damages.
 All rights reserved in the event of the grant of a patent, utility model or design. Copyright © Alfred Kärcher GmbH & Co. KG

4	3	2	1
---	---	---	---



Benennung / description
 HD 1050 B
 HD 1050 B

Material-Nr. / material no.
 1.810-972.0

F

IMPORTANT NOTE
 Data is intended for Kärcher Service only
 and must not be passed on to unauthorised third parties!

Version description		HD 1050 B
Version description		HONDA
Version description		1) 3200-3400
Pump-/motor speed at closed gun (circuit service)	l/min.	2000-2500
Pump		
High pressure nozzle (US-gpm at 40 psi)	US-gpm	25047
Flow rate, full load Pressure water	l/h	>860
Flow rate, partial load	l/h	400-450
Detergent 1 flow rate Full load	l/h	>25
Pressure full load GA Pressure water with Testing manometer	MPa	>19
Pressure half load GA	MPa	3-5
Pressure adjustment Servopress GA with Testing manometer	MPa	20,8-21,2
Working pressure full load Standard gun, new nozzle (Testing manometer)	MPa	>19
Pressure full load Device manometer	MPa	>23
Emission sound pressure level		
Sound level	dB(A)	108

E

D

C

B

A

X		document		number	type	version	status	sheet	of
Technical specificatio				5447220	TDA	00	FR	1	1
Datum date	Gezeichnet drawn by	Geprüft checked by	Normgeprüft std. checked by	Änderung / Engineering change			Ersatz für / replaces		
2015-01-21	AW03274	-----	-----	index	Anzahl / count	number	Datum / date	index	
4	3	2	1						