

## Cold water compact class

### HD 6/15 C Plus

#### Overview

Cold-water high-pressure cleaner for daily commercial use. With its compact dimensions, robust construction and greatest possible manoeuvrability, this unit is a credit to the compact class.

Order no. 1.150-603.0



#### Standard accessories

Trigger gun Easy Press, Trigger gun with soft grip, High-pressure hose 10m, Spray lance 850mm, Triple nozzle/Power nozzle Manual, Triple nozzle (0°/25°/40°) Manual, Dirt Blaster, Anti-twist system (AVS), Pressure switch control, Stainless steel spray lance 850mm

#### Technical data

Quantity of current phase Ph	1
Frequency Hz	50
Voltage V	230
Water flow rate l/h	230-560
Pressure bar/MPa	30-150/3-15
Max. Water feed temperature °C	up to 60
Connected load kW	3,1
Weight kg	28,3
Dimensions (L x W x H) mm	375x360x935

#### Description

This cold-water pressure washer with an alternating current drive unit is the ideal entry-level model for commercial end customers.

The upright HD 6/15 C Plus boasts impressive mobility, compactness and a height-adjustable shaped aluminium push handle. The advantage of the push handle is that it can easily be adjusted to the operator's height without using tools.

In the extended position, the unit's generous stowage facilities ensure that accessories are always ready to hand and put away safely. When retracted, this handy unit can be stowed easily in any estate care or service vehicle.

The washer boasts familiar KÄRCHER features such as a full shock-resistant plastic covering that protects the high-pressure pump and the motor from damage and soiling. Other very good features are an electric cable retractor (with plug lock) and a nozzle compartment arranged practically on the back of the unit.

## Cold water compact class

### HD 6/15 C Plus



The cleaner comes with a three-way nozzle that enables the water jet to be adjusted quickly and easily. You can choose between a high-pressure pencil jet, a high-pressure fan jet (25°) and a low-pressure fan jet. The low-pressure fan jet (40°) is used for dispensing cleaning agent. The cleaning agent metering valve enables cleaning agent to be mixed continuously with the high-pressure jet.

The large-volume oil container, which is very important for ensuring that the unit is always adequately lubricated, can be checked very easily from outside through an oil level inspection glass.

The three-piston axial pump with stainless steel pistons and a brass cylinder head guarantees a long service life and low susceptibility to faults. The special feature of this newly developed pump is that both the water inlet and the high-pressure outlet are made of brass, which makes them highly resistant to fracture and corrosion.

### Application

Suitable for use in many fields:  
crafts,  
trades,  
cleaning companies,  
local authorities

### Features & Benefits

Brass cylinder head with stainless steel inlet and pressure valves and safety valve  
High grade materials for a long service life

Easy Press trigger gun  
reduces holding and operating effort

Infinitely variable adjustment of pressure and water flow rate on the unit  
Allows adjustment of pressure and water flow on the unit allows to adjust the unit to different cleaning tasks

pressure switch  
Automatic switch-off of electric motor when gun is closed, energy is saved

Stabiler, ausziehbarer Schubbügel (aus Alu)  
Übernimmt im ausgefahrenen Zustand die Funktion der Zubehöraufnahme und gewährleistet eine problemlose Manövrierfähigkeit. Im eingefahrenen Zustand problemloser Transport z.B. im Servicefahrzeug/Kombi möglich.

Three-piston axial pump with hardened stainless steel pistons, swash-plate drive system  
Direct drive with minimum of moving parts, optimum efficiency, long service life

## Cold water compact class

### Adapter für Druckregelstrahlrohr

#### Adapter for variable pressure spray lance

For items 9, 10, for mounting accessories to lance, M 24/18 x 1.5  
Order no. 4.762-075.0



### Boron carbide nozzle

#### Boron carbide nozzle

(In addition to nozzle packs. Very wear-resistant nozzle for continuous-duty operation.)  
Order no. 6.415-084.0



### Dirt Blaster

#### Dirt Blaster

New Dirt Blaster generation with max. 180 bar/60°C, not adjustable  
Order no. 4.767-022.0



### Dirt Blaster, not adjustable

#### Dirt Blaster, without changeover

Ceramic nozzle and bearing ring  
Order no. 4.763-931.0



### Easy Foam Set

#### Easy Foam Set

Complete, ready-to-use HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve.  
Order no. 2.640-691.0



## Cold water compact class

### HD 6/15 C Plus

#### Fine mesh water filter

##### Fine mesh water filter

Mounted to machine inlet, 80 øm  
Order no. 4.730-102.0



#### Flächenreiniger FR 30 ME

##### Surface cleaner, 300 mm diameter

A rotating nozzle beam with Kärcher Power nozzles has an area coverage up to 10 times larger than conventional methods. Stainless steel version. Ceramic bearings. Integral vacuum connection.  
Order no. 2.640-355.0



#### Foam nozzle mounting kit

##### Anbausatz Schaumdüse

For applying foam detergent in metered quantities in sanitary and food areas, or where long reaction time is necessary, mounts to spray lance in place of HP nozzle  
Order no. 2.637-926.0



#### Geka coupling

##### Geka coupling

with female thread  
Order no. 6.388-473.0



##### Geka coupling

with hose liner  
Order no. 6.388-461.0



##### Geka coupling

with hose liner  
Order no. 6.388-455.0



## Cold water compact class

### HD 6/15 C Plus

#### High pressure hoses

##### High-pressure hose

Food industry version, AVS connection in trigger gun grey ID 6/155 °C/230 bar  
Order no. 6.390-445.0



##### High-pressure hose

With patented AVS connection in trigger gun (pivot mounted ) and hand screw union. M22x1.5 with anti-kink protection ID 6/155°C/250 bar  
Order no. 6.390-174.0



##### High-pressure hose 20 m, DN 8, PN 200 bar

With M 22x1.5 union at both ends and anti-kink protection ID 8/155°C/315 bar  
Order no. 6.390-031.0



##### High-pressure hose 20 m, DN 10, PN 400 bar, Longlife, extension

Longlife 400, With rotary coupling 2 x M22 x 1.5, ID 8/155°C/400 bar  
Order no. 6.390-027.0



##### High-pressure hose 10 m, DN 10, PN 400 bar, Longlife, extension

Longlife 400, Without rotary coupling 2 x M22 x 1.5, ID 8/155°C/400 bar  
Order no. 6.390-026.0



##### High-pressure hose

With M 22x1.5 union at both ends and anti-kink protection ID 10/155 °C/220 bar  
Order no. 6.390-023.0



##### High-pressure hose, 15 m, DN 8, 315 bar, extension

With M 22x1.5 union at both ends and anti-kink protection ID 8/155 °C/315 bar  
Order no. 6.390-010.0



##### High-pressure hose 10 m, DN 8, PN 315 bar, extension

With M 22x1.5 union at both ends and anti-kink protection ID 8/155°C/315 bar  
Order no. 6.389-891.0



## Cold water compact class

### HD 6/15 C Plus

#### High-pressure hose

With patented AVS connection in trigger gun (pivot mounted ) and hand screw union. M22x1.5 with anti-kink protection ID 6/155°C/250 bar  
Order no. 6.389-853.0



#### High-pressure hose, 20 m, DN 8, PN 180 bar, food version, extension

Food industry version with M 22x1.5 union at both ends, anti-kink protection, ID 8, with rotary coupling, for food industry, up to 230 bar  
Order no. 6.389-581.0



#### High-pressure hose, 10 m, DN 8, extension, food version

Food industry version with M 22x1.5 union at both ends, anti-kink protection, ID 8, with rotary coupling, for food industry, up to 230 bar  
Order no. 6.389-479.0



#### High-pressure hose, 10 m, DN 8, incl. swivelling joint

Longlife 400, With rotary coupling 2 x M22 x 1.5, ID 8/155°C/400 bar  
Order no. 6.388-083.0



### HP detergent injector

#### HP detergent injector

Adds up to 5% detergent in high-pressure mode  
Order no. 3.637-170.0



### Inno Foam Set

#### Inno Foam Set

Complete, ready-to-use HP foam system for use with mobile and stationary HD/HDS units for cleaning and disinfection. Twin spray lance with foam nozzle and changeover to HP jet for clear rinsing etc., HP chemical injector with precision 0-5% metering valve.  
Order no. 2.640-151.0



## Cold water compact class

### HD 6/15 C Plus

#### Installationsmaterial

##### Rotating joint

Reliably prevents HP hose twisting. M 22x1.5 connection with protector  
Order no. 4.401-076.0



#### Kugeldüsenträger

##### Rollover nozzle holder

Changes from solid to fan jet with flick of the wrist. Knurled nut for changeover to low pressure chemical intake, without nozzles (order Kärcher Power nozzle separately)  
Order no. 4.764-012.0



#### Kupplung

##### Double pipe union

For connecting and extending HP hoses. 2 x M22 x 1,5 connections, brass with rubber protector  
Order no. 4.403-002.0



#### Machine-specific nozzle kit

##### Machine-specific nozzle kit

detergent injector + HP nozzle + union  
Order no. 4.769-045.0



##### Power nozzle with union

for item 2.838-821 and 2.640-355  
Order no. 2.640-401.0



## Cold water compact class

### HD 6/15 C Plus

#### Nozzle pack for wet-blasting attachment

##### Nozzle pack for wet-blasting attachment

Nozzle pack for wet-blasting attachment, for items 29/30. Consisting of wet-blasting nozzle and nozzle insert, only for use with wet-blasting attachment

4762-010/-022

Order no. 2.638-526.0



#### Pipe cleaning hose, ID 6

##### Pipe cleaning hose, ID 6

Very flexible high-pressure hose for pipe cleaning (1/8"connection for nozzle)

Order no. 6.390-029.0



##### Pipe cleaning hose, ID 6

Very flexible high-pressure hose for pipe cleaning (1/8"connection for nozzle)

Order no. 6.390-028.0



#### Pipe cleaning nozzle

##### Pipe cleaning nozzle

With female thread, different spraying directions for environment-friendly cleaning of blocked drains and pipes. Nozzle orifices are positioned so that nozzle pulls itself and the hose into the pipe 4 rotating jets

Order no. 6.415-428.0



##### Pipe cleaning nozzle

With female thread, different spraying directions for environment-friendly cleaning of blocked drains and pipes. Nozzle orifices are positioned so that nozzle pulls itself and the hose into the pipe. 1x forwards, 3x30° backwards,

€ 30 mm

Order no. 5.763-017.0





## Cold water compact class

### HD 6/15 C Plus

#### Pipe cleaning nozzle

With female thread, different spraying directions for environment-friendly cleaning of blocked drains and pipes. Nozzle orifices are positioned so that nozzle pulls itself and the hose into the pipe. 3 x 30 °backwards, € 16 mm  
Order no. 5.763-015.0



#### Pivoting spray lance

##### Pivoting spray lance

Spray lances in various lengths, stainless steel with hand screw union.  
Ergonomically shaped handle mouldings for optimum control and insulation.  
Can be turned 360° under pressure.  
Order no. 4.760-550.0



##### Spray lance, 2040 mm, rotatable

Spray lances in various lengths, stainless steel with hand screw union.  
Ergonomically shaped handle mouldings for optimum control and insulation.  
Can be turned 360° under pressure.  
Order no. 4.760-366.0



##### Spray lance, 1500 mm, rotatable

Spray lances in various lengths, stainless steel with hand screw union.  
Ergonomically shaped handle mouldings for optimum control and insulation.  
Can be turned 360° under pressure.  
Order no. 4.760-365.0



##### Pivoting spray lance

Spray lances in various lengths, stainless steel with hand screw union.  
Ergonomically shaped handle mouldings for optimum control and insulation.  
Can be turned 360° under pressure.  
Order no. 4.760-364.0



##### Pivoting spray lance

Spray lances in various lengths, stainless steel with hand screw union.  
Ergonomically shaped handle mouldings for optimum control and insulation.  
Can be turned 360° under pressure.  
Order no. 4.760-386.0



## Cold water compact class

### HD 6/15 C Plus

#### Push-on washing brush

##### Push-on washing brush

Order no. 4.762-324.0



#### Rotary washing brush

##### Rotary washing brush

Driven by water jet. Gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 85 °C. M 18 x 1.5. (replaceable brush element)  
Order no. 4.762-288.0



##### Rotary washing brush

Driven by water jet. Gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 85 °C. M 18 x 1.5. (replaceable brush element)  
Order no. 4.762-284.0



#### Self-winding hose reel for wall mounting

##### Add-on kit wall fastening hose reel

Add- on kit to fasten a hose reel at the wall.  
Order no. 2.639-931.0



##### Hose reel without hp-hose, automatic

Self-winding hose reel (without HP hose) Kärcher HD hose plug-in system  
Order no. 2.639-919.0



#### Spray lance

##### Spray lance, 250 mm, fixed

Stainless steel with hand screw union, does not pivot In conjunction with extended trigger gun  
Order no. 4.760-058.0



## Cold water compact class

### HD 6/15 C Plus

#### Starting current limiter

##### Starting current limiter

Reduces starting current in single-phase supply and protects line fuse.

Order no. 2.637-495.0



#### Suction filter

##### Suction filter

With/without non-return valve, brass

Order no. 4.730-019.0



##### Suction filter

With/without non-return valve, brass

Order no. 4.730-012.0



#### Triple nozzle , touchless changeover

##### Triple nozzle , touchless changeover

Fast and easy jet changeover by flicking the nozzle. Choose from high-pressure pencil jet, high-pressure fan jet and low-pressure fan jet. On machines with injector, the low-pressure is used for picking up and applying detergent. M18 x 1.5 connection.

Order no. 4.767-001.0



#### Unterbodenstrahlrohr

##### Underbody lance

Mobile. For effective and convenient cleaning of underbodies and wheel arches. Stainless steel. Without HP nozzle

Order no. 4.760-245.0



## Cold water compact class

### HD 6/15 C Plus

#### Variable pressure spray lance

##### Variable pressure spray lance

With integral pressure gauge for infinitely variable pressure control directly on lance. Nozzle connection M 24 x 1.5. Chemical feed in low pressure mode. Variable pressure lance and Kärcher Power nozzle.  
Order no. 4.760-362.0



##### Variable pressure spray lance

With integral pressure gauge for infinitely variable pressure control directly on lance. Nozzle connection M 24 x 1.5. Chemical feed in low pressure mode. Variable pressure lance and Kärcher Power nozzle.  
Order no. 4.760-230.0



#### Verbindungsstück

##### Adapter

For connecting HP nozzles and accessories directly to trigger gun ( with nozzle union) 1 x M22 x 1.5/ 1 x M18 x 1.5  
Order no. 4.402-022.0



#### Water supply hose

##### Water supply hose

ID 19 R1"/R 3/4" - up to 85°C - for suction mode  
Order no. 4.440-207.0



##### Water supply hose

ID13 R1"/R 3/4" - up to 30°C  
Order no. 4.440-038.0



#### WC-Strahlrohr

##### WC-Spray lance

With nozzle. Specially shaped for cleaning WCs. Stainless steel.  
Order no. 4.760-073.0



Cold water compact class

HD 6/15 C Plus

### Wet blasting attachment

#### Wet-blasting attachment (without nozzles)

Adds abrasive to high-pressure jet. For removing paint, rust, scale. Mounts to spray lance in place of HP nozzle. Without abrasive flow control  
Order no. 4.762-022.0



#### Wet blasting attachment ( without nozzles)

Adds abrasive to high-pressure jet. For removing paint, rust, scale. Mounts to spray lance in place of HP nozzle. With abrasive flow control  
Order no. 4.762-010.0

