HD 10/15-4 Cage Food





Unheated high-pressure cleaners for universal commercial use in the food sector.



Cage version

- Non-rusting stainless steel panels.
- Protection for all components.

3 Pump kit

4-pole electric motor with three-piston axial pump.

Ceramic pistons.

Pump kit

- 4-pole electric motor with three-piston axial pump.
- Ceramic pistons.

4 Complies with the most rigorous hygiene requirements

- Non-rusting stainless steel panels.
- All parts in contact with water are made from special food-safe brass.

Technical Data and Equipment

KARCHER



HD 10/15-4 Cage Food

- Grease-resistant high-pressure hose
- High-end spray attachment
 Two cleaning agent tanks with clear rinse function

Technical data		
Order no.		1.524-232.0
EAN code		4039784732513
Supply voltage	Ph / V / Hz	3 / 400 / 50
Flow rate	l/h	440–990
Working pressure	bar / MPa	20–145 / 2–14.5
Working pressure	PSI	290290 / 2100
Max. pressure	bar / MPa	175 / 17.5
Max. water inlet temperature	°C	85
Connection load	kW	6.4
Weight	kg	68
Dimensions (L × W × H)	mm	650 × 521 × 1100
E an dia managent		
Equipment		
Equipment Spray gun		Industrial trigger gun
	m	Industrial trigger gun 10 / Food industry version
Spray gun	m mm	
Spray gun Pressure hose		10 / Food industry version
Spray gun Pressure hose Spray lance		10 / Food industry version 1050
Spray gun Pressure hose Spray lance Power nozzle		10 / Food industry version 1050
Spray gun Pressure hose Spray lance Power nozzle Anti-twist system		10 / Food industry version 1050
Spray gun Pressure hose Spray lance Power nozzle Anti-twist system Pressure cut-off Enclosed tubular frame construction with integrated crane attachment		10 / Food industry version 1050



		Order no.	ID	Max. working pressure	Length		Price	Description	
Longlife food design with screw c	onnec	tions at both en	ds			<u> </u>	<u> </u>		
High-pressure hose food industry 400 bar, 20 m, ID 8, including rotary coupling		6.391-887.0	ID 8	400 bar	20 m			Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5	
High pressure hose food ID 8, 10 m	2	6.391-864.0	ID 8	400 bar	10 m				
Special hoses									
High-pressure hose 1.5 m, ID 8, including connectors, outlet bend	3	6.388-886.0	ID 8	400 bar	1.5 m				

KARCHER



		Order no.			Price	Description
Nozzle union						
Nozzle union food industry	1	5.401-318.0				Made of special brass alloy for use in the food industry.
Spacer (including nozzle union)						
Spacer (includes nozzle screws)	2	5.394-294.0				Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces.
Rotary coupling						
Rotary coupling	3	4.401-091.0				Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.
Coupling						· · · · · · · · · · · · · · · · · · ·
Coupler -2xM22x1,5	4	4.403-002.0				Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M □ 22 x 1.5 m.
Connector						
Nozzle screws / screw socket	5	4.402-022.0				Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1x M 22 x 1.5$ and $1x M 18 x 1.5$.
Coupling parts						
Articulated joint	6	6.987-705.0				This articulated joint with variable angle adjustment (up to an angle of 120°) is recommended for cleaning hard to reach areas. Fits directly on the spray lance.



		Order no.	Flow rate		Price	Description	
Servo control			1100 1000		11100		
Servo control, stainless steel ver- sion	1	4.775-800.0	750–1100 l/h				
Trigger guns							
High-end HP Food trigger gun	2	4.775-825.0					
High-end HP trigger gun	3	4.775-823.0					
Quick connect							
Quick coupling	4	6.401-458.0				For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1,5 female.	
Male coupling	5	6.401-459.0				Hardened stainless steel nipple for quick coupling 6.401-458. With M22 x 1,5 male.	



		Order no.	Nozzle size		Price	Description	
Power nozzle spray angle 25°			-				
Power nozzle spray angle 25°	1	2.883-403.0	65			Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	
Power nozzle spray angle 40°							
Power nozzle spray angle 40°	2	2.884-526.0	75			Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	
HP nozzle spray angle 0°							
High-pressure nozzle with 0° spray angle	3	2.884-537.0	60			Solid jet for very stubborn dirt and stains.	
Power nozzle spray angle 15°							
Power nozzle spray angle 15°	4	2.883-392.0	70			Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	

□ Available accessories. ▲ Extension hose cluded in delivery.

KARCHER

Accessories for HD 10/15-4 Cage Food 1.524-232.0



		Order no.	Max. working pressure	Length		Price	Description	
Rotating spray lances								_
Spray lance, grey, 1050 mm, rotata- ble	1	4.760-655.0	300 bar	1050 mm			1050 mm grey, rotatable food-grade lance for use in the food industry. All parts coming into contact with water are food safe.	
600 mm spray pipe, rotatable	2	4.760-664.0	300 bar	600 mm			600 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	
850 mm spray pipe, rotatable	3	4.760-663.0	300 bar	850 mm			850 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	
1050 mm spray pipe, rotatable	4	4.760-660.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	
1550 mm spray pipe, rotatable	5	4.760-661.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	
2050 mm spray pipe, rotatable	6	4.760-662.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	
Double lance								
Double lance 960 mm	7	6.394-665.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance								
Spray lance for toilets and rain gutters	8	4.760-073.0					Stainless steel lance WC and gutter with nozzle insert. Spe- cially shaped for effective and hygienic cleaning of gutters and toilets.	1 🗆
Flexible spray lance								
Flexible lance 1050 mm	9	6.394-654.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
Undercarriage spray lance		1	1	1	1 1	1		
Underbody lance	10	4.760-245.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Spray lances			0501	0.50	1 1	1		
Vibrasoft lance	11	6.415-951.0	250 bar	950 mm			The spring-loaded 360° loop handle significantly reduces the vibrations on the spray lance, reducing the physical burden or the user, e.g. when working with the dirt blaster.	ם ו
Spray lance								
250 mm lance, non-rotatable	12	4.760-667.0		250 mm			250 mm stainless steel lance. With manual coupling. Non-ro- tatable.	
Telescopic spray lance		1	1	1	1 1	1		
Telescopic spray lance	13	6.394-690.0	225 bar					
Strap for telescopic spray pipe	14	6.373-987.0					Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.	
Gutter cleaner								
Gutter cleaning lance	15	2.642-305.0					The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	



					Diame-		
		Order no.	Flow rate	Nozzle size	ter	Price	Description
FR 30 Me surface cleaner							
Hard surface cleaner FR 30 Me	1	2.640-355.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.
Hard surface cleaner FR 50							
Hard surface cleaner FR 50	2	2.640-679.0			500 mm		Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.
Machine-specific nozzle kits for	FR						
Nozzle kit for surface cleaners	3	2.640-442.0	850–1100 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).
Hard surface cleaner FRV 30							
FRV 30 surface cleaner	4	2.642-999.0					
Rubber lip for FRV 30	5	2.642-910.0					For smooth floors indoors. The squeegee increases the suc- tion performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.
FRV 30 Me surface cleaner			- ÷	*	· · ·		· ·
FRV 30 Me	6	2.642-911.0					

KARCHER



		Orderen	Max. working							
		Order no.	Max. working pressure	Nozzle size	Diame- ter		Price	Description		
Barrel and tank cleaning				1			1	1		
Barrel cleaner BC 14/12	1	2.641-740.0	120 bar					The BC 14/12 is an spray system for the efficient interior cleaning of containers and barrels##, specially oak barrels with a volume of between 225 and 600 litres. One cleaning cycle is completed within 36 seconds and every spot in the container is covered by a water jet. After cleaning is finished the BC 14/12 can easily and conveniently take up the dirty water. The transformer included with the BC 14/12 makes it possible to use it worldwide (110 - 240 V, 50 - 60 Hz). The nozzle kits included make possible use with high-pressure cleaners with a water volume of 600 to 1400 I / h. Electrical components are protected in accordance with IP 55.		
Pipe cleaning hose, ID 6				1					-	
Pipe cleaning hose, DN 6, 20 m, max. 120 bar	2	6.390-028.0	120 bar					The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).		
Pipe cleaning hose, DN 6, 30 m, max. 120 bar	3	6.390-029.0	120 bar					30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).		
Pipe cleaning hose, DN 6, 20 m, max. 250 bar	4	6.390-030.0	250 bar					The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).		
Pipe cleaning nozzle										
Pipe cleaning nozzle	5 6	5.763-019.0 5.763-020.0		65 65	16 mm 16 mm			16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.		
	7	5.763-021.0		70	30 mm			30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.		
Rotating pipe cleaning nozzle	8	6.415-440.0		65	16 mm			Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.		
Pipe cleaning dirt blaster D 25 / 060	9	6.415-945.0		60	25 mm			The forward-tilted rotating pencil jet removes the most stub-		
Pipe cleaning dirt blaster D 30 / 060		6.415-947.0		60	30 mm			born dirt. The three backwards-tilted jets ensure the neces-		
Pipe cleaning dirt blaster D 35 / 060	11	6.415-949.0		60	35 mm			sary forward movement, as well as convenient handling.		



		Order no.	Max. working pressure	Nozzle size		Price	Description
Triple nozzles		<u> </u>	<u> </u>			1	
Triple jet nozzle 060	1	4.767-157.0	300 bar	60			Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.
Triple nozzle, touchless changeov	ver						
Triple nozzle, touchless changeover	2	4.767-067.0		60			Triple nozzle with high-pressure pencil jet, high pressure fan jet (25°) with power nozzle and low-pressure fan jet (40°). Fast and easy jet changeover by turning the nozzle.
Dirt blaster, large							
Dirt blaster	3	4.763-254.0	300 bar	70			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.
Dirt blaster - with changeover to le	ow pr	essure cleaning	agent intake				
Dirt blaster - with changeover to low pressure cleaning agent intake	4	4.763-952.0	300 bar	70			Dirt blaster – rotating pencil jet – 10x cleaning power. Ceramic nozzle and bearing ring for long service life. Changeover to detergent intake (low pressure) max. 300 bar/30 MPa, 85 °C
Dirt blaster with changeover to far	1 jet	~	~	-			
Dirt blaster with changeover to fan jet	5	4.763-958.0	300 bar	70			Dirt blaster – rotating pencil jet – 10x cleaning power. Ceramic nozzle and bearing ring for long service life. Changeover to high-pressure fan jet max. 300 bar/30 MPa, 85 °C



		Order no.	Nozzle size		Price	Description
Wet blasting attachment (without	nozzle					
Wet blasting attachment with flow control (without nozzles)	1	4.762-010.0				Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abrasive to the high-pressure jet.
Wet blasting attachment without flow control (nozzles not included)	2	4.762-022.0				Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.
Nozzle kits for wet jet unit						
Nozzle kits for wet jet unit 065	3	2.637-905.0	65			Consisting of wet-blasting nozzle and nozzle insert, only for use with wet-blasting attachment 4762-010/-022
Boron carbide nozzle				 î		
Boron carbide nozzle, for machines up to 1,000 l/h	4	6.415-084.0	6 mm			In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.



		Order no.	Flow rate			Price	Description	
Cup foam lance								
Cup foam lance	1	6.394-668.0	1200 l/h				Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.	
1-litre cleaning agent container for foam lance	2	6.414-954.0						
Inno Foam Kit								
Inno Foam Set	3	2.640-692.0					High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	C
Easy Foam Set							· •	
Easy Foam Set	4	2.640-693.0					HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	
Nozzle kits for Inno/Easy Foam S	et							
Nozzle kit 090 for Inno / Easy Set 700–1,000 l/h	5	2.640-688.0	700–1000 l/h				Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 l/h. For optimal foam sys- tem performance.	
Foam nozzle mounting kit					-	-		
Foam nozzle attachment kit	6	2.637-926.0					Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	

KARCHER



		Order no.	Length		Price	Description	
Automatic, self-winding hose reels	;						-
Automatic hose reel, coated	1	2.639-919.0	20 m			Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	
Powder-coated swivel holder	2	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	
Automatic hose reel, stainless steel, includes swivel holder	3	6.391-421.0	20 m			Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
ABS automatic stainless steel hose drum	4	2.641-866.0	20 m			High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Con- nection for HP hoses with nipple.	
ABS pivoting stainless steel wall bracket	5	2.641-867.0				Swivelling wall bracket made of high-grade steel (for 2.641- 866). This makes maximum flexibility and convenience possi- ble when working with the HP hose.	
Automatic hose reel, powder-coat- ed steel / plastic	6	6.392-975.0	20 m			Automatic hose reel for 20 m high-pressure hose. The con- sole is made from powder-coated steel, the drum is made from plastic.	
Automatic stainless steel / synthetic material hose drum	7	6.392-965.0	20 m			Automatic hose reel for 20 m high-pressure hose. The con- sole consists of stainless steel, the drum is made from plastic	



		Order no.	Flow rate				Price	Description	
Push-on washing brush									
Push-on washing brush	1	4.762-016.0						Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	
Rotating washing brush									
Rotating washing brush for > 800	2	4.762-559.0	900–1300 l/h						
l/h machines	3	4.762-562.0	900–1300 l/h						
■ Included in delivery. □ Available accessories. ▲ Extension hose.									

HD 10/15-4 Cage Food, 1.524-232.0, 2015-12-11

				,	 · · · · · · · · · · · · · · · · · · ·		
		Order no.				Price	Description
		Order no.				Price	Description
Chemical take up set							
Chemical take up set	1	2.641-944.0					
Foam lance holder set							
Foam lance holder set	2	2.641-947.0					
Included in delivery.	Available acc	essories.	xtension hose.				



		,							
		Order no.	Length	Diameter			Price	Description	
Suction filter			•	•	·				
Water suction filter	1	6.414-956.0						[
In all rate of the stationers.	in defining 🔲 Analishing second in A. Extension have								