

Compliance with the current version of Kärcher standard KÄN 050.032 Constituent substances (ban of lead, cadmium, etc.) must be guaranteed. Standard date format according to ISO 8601 (YYYY-MM-DD).
 The reproduction, distribution and utilization of this document as well as the communication of its contents to others without explicit authorization is prohibited. Offenders will be held liable for the payment of damages.
 All rights reserved in the event of the grant of a patent, utility model or design. Copyright © Alfred Kärcher GmbH & Co. KG

4	3	2	1																																																																																												
KÄRCHER [®]	Benennung / description HD 5/15 CX Plus*EU HD 5/15 CX Plus*EU		Material-Nr. / material no. 1.520-141.0																																																																																												
Winnenden			F																																																																																												
IMPORTANT NOTE Data is intended for Kärcher Service only and must not be passed on to unauthorised third parties!																																																																																															
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 40%;">Mains supply</td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> <td style="width: 40%;"></td> </tr> <tr> <td>Supply voltage / phases</td> <td>V / Ph</td> <td></td> <td>230/1</td> </tr> <tr> <td>Mains voltage, permissible Voltage tolerance Voltage min Voltage max</td> <td>V</td> <td></td> <td>216-244</td> </tr> <tr> <td>Frequency</td> <td>Hz</td> <td></td> <td>50</td> </tr> <tr> <td>Connection power max.</td> <td>kW</td> <td></td> <td></td> </tr> <tr> <td>Electro motor</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Testing voltage with testing period 1sec.</td> <td>mA</td> <td></td> <td></td> </tr> <tr> <td>Current pickup, full load (after 5 min)</td> <td>a</td> <td></td> <td><14,5</td> </tr> <tr> <td>Motor protection switch Adjustment valueEinstellwert</td> <td>a</td> <td></td> <td></td> </tr> <tr> <td>Electric motor speed</td> <td>rpm</td> <td></td> <td></td> </tr> <tr> <td>High-pressure pump oil volume</td> <td>l</td> <td></td> <td>0,14</td> </tr> <tr> <td>High-pressure pump oil type</td> <td>type</td> <td></td> <td>SAE15W40</td> </tr> <tr> <td>Feed pressure water</td> <td>MPa</td> <td></td> <td></td> </tr> <tr> <td>min. feed water volume</td> <td>l/min</td> <td></td> <td>720</td> </tr> <tr> <td>max. feed temperature water</td> <td>°C</td> <td></td> <td>60</td> </tr> <tr> <td>High pressure nozzle (US-gpm at 40 psi)</td> <td>US-gpm</td> <td></td> <td>032</td> </tr> <tr> <td>Flow rate, full load Pressure water</td> <td>l/h</td> <td></td> <td>480-500</td> </tr> <tr> <td>Flow rate, full load Suction water</td> <td>l/h</td> <td></td> <td></td> </tr> <tr> <td>delivery servo press</td> <td>l/h</td> <td></td> <td></td> </tr> <tr> <td>Flow rate, partial load</td> <td>l/h</td> <td></td> <td></td> </tr> <tr> <td>Detergent 1 flow rate Full load</td> <td>l/h</td> <td></td> <td>>20</td> </tr> <tr> <td>Working pressure full load Standard gun, new nozzle (Testing manometer)</td> <td>MPa</td> <td></td> <td></td> </tr> <tr> <td>Working pressure partial load (Testing manometer)</td> <td>MPa</td> <td></td> <td></td> </tr> </table>				Mains supply				Supply voltage / phases	V / Ph		230/1	Mains voltage, permissible Voltage tolerance Voltage min Voltage max	V		216-244	Frequency	Hz		50	Connection power max.	kW			Electro motor				Testing voltage with testing period 1sec.	mA			Current pickup, full load (after 5 min)	a		<14,5	Motor protection switch Adjustment valueEinstellwert	a			Electric motor speed	rpm			High-pressure pump oil volume	l		0,14	High-pressure pump oil type	type		SAE15W40	Feed pressure water	MPa			min. feed water volume	l/min		720	max. feed temperature water	°C		60	High pressure nozzle (US-gpm at 40 psi)	US-gpm		032	Flow rate, full load Pressure water	l/h		480-500	Flow rate, full load Suction water	l/h			delivery servo press	l/h			Flow rate, partial load	l/h			Detergent 1 flow rate Full load	l/h		>20	Working pressure full load Standard gun, new nozzle (Testing manometer)	MPa			Working pressure partial load (Testing manometer)	MPa		
Mains supply																																																																																															
Supply voltage / phases	V / Ph		230/1																																																																																												
Mains voltage, permissible Voltage tolerance Voltage min Voltage max	V		216-244																																																																																												
Frequency	Hz		50																																																																																												
Connection power max.	kW																																																																																														
Electro motor																																																																																															
Testing voltage with testing period 1sec.	mA																																																																																														
Current pickup, full load (after 5 min)	a		<14,5																																																																																												
Motor protection switch Adjustment valueEinstellwert	a																																																																																														
Electric motor speed	rpm																																																																																														
High-pressure pump oil volume	l		0,14																																																																																												
High-pressure pump oil type	type		SAE15W40																																																																																												
Feed pressure water	MPa																																																																																														
min. feed water volume	l/min		720																																																																																												
max. feed temperature water	°C		60																																																																																												
High pressure nozzle (US-gpm at 40 psi)	US-gpm		032																																																																																												
Flow rate, full load Pressure water	l/h		480-500																																																																																												
Flow rate, full load Suction water	l/h																																																																																														
delivery servo press	l/h																																																																																														
Flow rate, partial load	l/h																																																																																														
Detergent 1 flow rate Full load	l/h		>20																																																																																												
Working pressure full load Standard gun, new nozzle (Testing manometer)	MPa																																																																																														
Working pressure partial load (Testing manometer)	MPa																																																																																														
E																																																																																															
D																																																																																															
C																																																																																															
B																																																																																															
A																																																																																															
		document	number	type	version	status	sheet	of																																																																																							
		Technical specificatio	5339730	TDA	03	FR	1	2																																																																																							
Datum date	Gezeichnet drawn by	Geprüft checked by	Änderung / Engineering change index Anzahl / count			Ersatz für / replaces Datum / date index																																																																																									
2013-09-02	AW03274	-----	-----																																																																																												
4	3	2	1																																																																																												

