

Technical Specification:**HD 7/18 CX Plus *EU****1.151-653.0****Pre - version**

Supply voltage / Phase	V / PH	400 / 3	V / PH	400 / 3
Supply voltage, allowable tolerance	V	376 - 424	V	376 - 424
Frequency	Hz	50	Hz	50
Current consumption, high-pressure (after 4 min.)	A	< 8,5	A	< 8,5
Motor protective switch adjustment	A	10	A	10
Connecting load	kW	4,7	kW	4,7
High-pressure nozzle (US-gpm at 40 psi)	Größe	042	size	042
Overflow valve opening pressure (testing pressure gauge)	bar	152 - 158	psi	2204 - 2291
High-pressure mode, handgun with new nozzle (testing pressure gauge)	bar	130 - 150	psi	1885 - 2175
Flow rate, high-pressure	l/min	10,58 - 11,33	USgpm	2,8 - 2,95
Flow rate cleaning agent, high-pressure	l/min	> 0,5	USgpm	> 0,1
High-pressure pump, oil type	SAE	90	SAE	90
High-pressure pump, oil quantity	Liter	0,35	fl.oz.	11,83
Water supply, pressure	bar	10	psi	145
Water supply, flow rate	l/min	13,33	USgpm	3,5
Water supply, temperature	C	60	F	140
Water supply, hose diameter	Zoll	3/4	in	3/4
Water supply, hose length	m	7,5	ft	24,608

FKV: 0.092-232.0

Stromlaufplan: 0.088-007.0

Stand: 02/06 SRP

FKV: 0.092-232.0

Circuit diagram: 0.088-007.0

Date: 02/06 SRP