

Printing date 17.05.2019 Version number 7 Revision: 09.10.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: RM 806 ASF NTA-free
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture High pressure cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Alfred Kärcher SE & Co. KG Alfred-Kärcher-Str. 28-40 D - 71364 Winnenden

Postfach 160 D - 71349 Winnenden Tel.: +49-7195-14-0

Fax: +49-7195-14-2212

www.karcher.com

Distributor:
Kaercher (UK) Ltd.
Kaercher House
Beaumont Road
Banbury
Oxon OX16 1TB
Great Britain

Tel.: +44-1295-752-000 *Fax:* +44-1295-266-436

· Further information obtainable from:

Department PCD-D Tel.: +49-7195-14-2548 Fax: +49-7195-14-3164 safetydata@karcher.com

· 1.4 Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

GB -



Printing date 17.05.2019 Version number 7 Revision: 09.10.2017

Trade name: RM 806 ASF NTA-free

(Contd. of page 1)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labelling:

sodium hydroxide

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

2.3 Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Cleaning agent

(Contd. on page 3)



Printing date 17.05.2019 Version number 7 Revision: 09.10.2017

Trade name: RM 806 ASF NTA-free

CAS: 15763-76-5	sodium p-cumenesulphonate	1-5%
EINECS: 239-854-6 Reg.nr.: 01-2119489411-37-xxxx	♠ Eye Irrit. 2, H319	
CAS: 1310-73-2	sodium hydroxide	2-<59
EINECS: 215-185-5 Index number: 011-002-00-6 Reg.nr.: 01-2119457892-27-xxxx	📀 Met. Corr.1, H290; Skin Corr. 1A, H314	
CAS: 78330-20-8	fatty alcohol ethoxylate	1-5%
	🧇 Eye Dam. 1, H318	
CAS: 69011-36-5	isotride can ole tho xylate + 8 EO	1-5%
EC number: 931-138-8 Reg.nr.: 02-2119552461-55-XXXX	� Eye Dam. 1, H318; ♦ Acute Tox. 4, H302	
Regulation (EC) No 648/2004 on a	letergents / Labelling for contents	
non-ionic surfactants, anionic surfa	uctants, polycarboxylates	<5%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information

Involve doctor immediately.

Immediately remove any clothing soiled by the product.

· After inhalation

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- · After skin contact Immediately wash with water and soap and rinse thoroughly.
- · After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- · 4.2 Most important symptoms and effects, both acute and delayed Corneal damage
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents Water with full jet.

(Contd. on page 4)



Printing date 17.05.2019 Version number 7 Revision: 09.10.2017

Trade name: RM 806 ASF NTA-free

(Contd. of page 3)

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear fully protective suit.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

 $Ensure\ a dequate\ ventilation.$

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with eyes and skin.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles:

Unsuitable material for receptacle: aluminium.

Store only in the original receptacle.

· Information about storage in one common storage facility:

Do not store together with acids.

Keep away from food, beverages and feed.

- · Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot 7.3 Specific end use(s) No further relevant information available.

GB

(Contd. on page 5)



Printing date 17.05.2019 Version number 7 Revision: 09.10.2017

Trade name: RM 806 ASF NTA-free

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

1310-73-2 sodium hydroxide

WEL Short-term value: 2 mg/m³

- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

Filter A/P2.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

· Protection of hands:



Protective gloves.

- · Material of gloves Butyl rubber, BR
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · For the permanent contact gloves made of the following materials are suitable:
 - * butyl rubber 0,7 mm, 480 min (EN 374)
- $\cdot \textit{As protection from splashes gloves made of the following materials are suitable:} \\$
- * nitril rubber 0,4 mm, 30 min (EN 374)
- · Eye protection:



Tightly sealed goggles (EN 166)

· Body protection:

Protective work clothing.

Boots

GB

(Contd. on page 6)



Printing date 17.05.2019 Version number 7 Revision: 09.10.2017

Trade name: RM 806 ASF NTA-free

(Contd. of page 5)

9.1 Information on basic physical and ca	hemical properties
General Information	F. vP
Appearance:	
Form:	Fluid
Colour:	Yellow
Odour:	citrus-like
Odour threshold:	Not determined.
pH-value at 20 °C:	13.3
pH-value 1 %:	12
Change in condition	
Melting point/freezing point:	-7.5 °C
Initial boiling point and boiling range	: 100 °C
Flash point:	Not applicable
Flammability (solid, gaseous)	Not applicable.
Ignition temperature:	not applicable
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	$1.133 \ g/cm^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic at 20 °C:	6 s (DIN 53211/4)
Solvent content:	
VOC (EC)	0.00 %
Solids content:	27.0 %



Printing date 17.05.2019 Version number 7 Revision: 09.10.2017

Trade name: RM 806 ASF NTA-free

(Contd. of page 6)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity corresponds to 10.3
- · 10.2 Chemical stability
- $\cdot \textit{Thermal decomposition / conditions to be avoided:} \\$

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Strong exothermic reaction with acids

Reacts with light alloys to form hydrogen

Corrodes aluminium

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

Not compatible with alkali-sensitive substances like Sn, Zn, Al and paintings.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

69011-36-5 isotridecanolethoxylate + 8 EO

Oral ATE 500 mg/kg (Rat)

- Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

1310-73-2 sodium hydroxide

LC50/96 h 125 mg/l (Gambusia affinis) EC50/48 h 76 mg/l (Daphnia magna)

(Contd. on page 8)



Printing date 17.05.2019 Version number 7 Revision: 09.10.2017

Trade name: RM 806 ASF NTA-free

	(Contd. of page 7)		
EC50/15 min	22 mg/l (Photobacterium phosphoreum)		
69011-36-5 is	otridecanolethoxylate + 8 EO		
LC50/96 h	1-10 mg/l (Leuciscus idus)		
EC50/48 h	1-10 mg/l (Aquatic invertebrates)		
EC50/72 h	1-10 mg/l (Aquatic plants)		
· 12.2 Persisten	· 12.2 Persistence and degradability		
69011-36-5 isotridecanolethoxylate + 8 EO			
Bismuth-act. sup. ≥90 % (mod. OECD 301 E)			

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · COD-value: 230000 mg/l
- · General notes:

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

The contained organic complexing agents reach a DOC-elimination grade of 80% (corresponding to No. 406 of Annex "Analytic and measuring methods") and with this meet the tightened demands of Annex 49 of the revised Direction on liqid waste.

In compliance with the prescribed application parameters, the product does not lead to stable emulsions.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

(Contd. on page 9)



Printing date 17.05.2019 Version number 7 Revision: 09.10.2017

Trade name: RM 806 ASF NTA-free

(Contd. of page 8)

· European waste catalogue

07 06 01* aqueous washing liquids and mother liquors

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product. Non contaminated packagings may be recycled.

· Recommended cleansing agents: Water, if necessary together with cleaning agents.

SECTION 14: Transport information		
· 14.1 UN-Number	VII.100.4	
· ADR, IMDG, IATA	UN1824	
· 14.2 UN proper shipping name		
$\cdot ADR$	1824 SODIUM HYDROXIDE SOLUTION	
· IMDG, IATA	SODIUM HYDROXIDE SOLUTION	
· 14.3 Transport hazard class(es)		
$\cdot ADR$		
· Class	8 (C5) Corrosive substances.	
· Label	8	
· IMDG, IATA		
<u> </u>		
· Class	8 Corrosive substances.	
· Label	8	
· 14.4 Packing group · ADR, IMDG, IATA	III	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Warning: Corrosive substances.	
· Danger code (Kemler):	80	
EMS Number:	F- A , S - B	
· Segregation groups	Alkalis	
· Stowage Category	A	
· Segregation Code	SG35 Stow "separated from" acids.	
	(Contd. on page 1	



Printing date 17.05.2019 Version number 7 Revision: 09.10.2017

Trade name: RM 806 ASF NTA-free

745 m	(Contd. of page
14.7 Transport in bulk according to A Marpol and the IBC Code	Annex II of Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000
	ml
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000
	ml
IATA	
Remarks:	Product ist corrosive to aluminium
· UN ''Model Regulation'':	UN 1824 SODIUM HYDROXIDE SOLUTION, 8
	III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. A product information sheet can be provided if requested.

· Relevant phrases

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

(Contd. on page 11)



Printing date 17.05.2019 Version number 7 Revision: 09.10.2017

Trade name: RM 806 ASF NTA-free

(Contd. of page 10)

H318 Causes serious eye damage. H319 Causes serious eye irritation.

· Department issuing SDS: PCD-D

· Contact:

Department PCD-D Tel.: +49-7195-14-2548 Fax: +49-7195-14-3164 safetydata@karcher.com

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Met. Corr.1: Corrosive to metals - Category 1

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

* Data compared to the previous version altered.

0.011-350.0 RM806/13 NTA-free 1.852