



4	3	2	1
 KÄRCHER Winnenden		Benennung HDS 8/17 C *EU-I	Material-Nr. 1.174-309.0

IMPORTANT NOTE
Data is intended for Kärcher Service only
and must not be passed on to unauthorised third parties!

Mains supply		
Supply voltage / phases	V / Ph	400/3
Mains voltage, permissible Voltage tolerance Voltage min Voltage max	V	376-424
Frequency	Hz	50
Connection power max.	kW	5,7
Electro motor		
Current pickup, full load (after 10 min)	a	<8,5
Electric motor speed	rpm	2800
Pump		
High-pressure pump oil volume	l	0,30
High-pressure pump oil type	type	SAE90
Feed pressure water	MPa	1,0
min. feed water volume	l/h	1000
max. feed temperature water	°C	30
High pressure nozzle (US-gpm at 40 psi)	US-gpm	045
Flow rate, full load Pressure water	l/h	707-750
delivery servo press	l/h	300-360
Flow rate, partial load	l/h	290-340
Detergent 1 flow rate Full load	l/h	>40
Working pressure full load, Standard gun, new nozzle (Testing manometer)	MPa	>14,9
Working pressure partial load (Testing manometer)	MPa	2,8-3,0
Safety valve Opening start (Testing manometer)	MPa	18,0-19,0
Overflow valve open. press. (Testing manometer)	MPa	16,9-17,3

		Dokument		Nummer		Art	Version	Status	Blatt	Blz.
		Technical specificatio		5344307		TDA	00	FR	1	2
Datum	Gezeichnet	Geprueft	Normgepr.	Aend.- Index	Anz. Aend.	Aenderungsnr.		Ersatz fuer		Ersatz f. Index
2013-01-07	AW03260	-----	-----							
4	3		2			1				

4	3	2	1
 KÄRCHER [®] Winnenden		Benennung HDS 8/17 C *EU-I	
		Material-Nr. 1.174-309.0	

Pressure switch 1 (on)	MPa	1
Pressure switch 2 (off)	MPa	1
Burner		
Burner water temperature - Increase, full load	K	58-62
Burner nozzle	gph	1,25
Steam nozzle Size US-gpm / 40psi	US-gpm	050
Fuel pump Adjustment pressure	MPa	1,4
max. air pressure on Burner cover	mmWs	35
Heating capacity	kW	58
Emissions - exhaust values		
Burner exhaust gas temperature	°C	200
Burner exhaust value CO2	%	10-11,5
Burner soot number	Value	0-1
Exhaust current	kg/s	0,0296
Emission sound pressure level		
Sound level	dB(A)	96

		Dokument		Nummer		Art	Version	Status	Blatt	Blz.
		Technical specificatio		5344307		TDA	00	FR	2	2
Datum	Gezeichnet	Gepueft	Normgepr.	Aend. Index	Anz. Aend.	Aenderungsnr.		Ersatz fuer		Ersatz f. Index
2013-01-07	AW03260	-----	-----							
4	3				2	1				