

Compliance with the current version of Kärcher standard KN 050.032 Constituent substances (ban of lead, cadmium, etc.) must be guaranteed. Standard date format according to ISO 8601 (YYYY-MM-DD). The reproduction, distribution and utilization of this document as well as the communication of its contents to others without explicit authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. Copyright © Alfred Kärcher GmbH & Co. KG

4	3	2	1
---	---	---	---



Benennung / description
 HD 10/21-4 S *EU-I
 HD 10/21-4 S *EU-I

Material-Nr. / material no.
 1.286-300.0

F
E
D
C
B
A

IMPORTANT NOTE
 Data is intended for Kärcher Service only
 and must not be passed on to unauthorised third parties!

Mains supply		
Supply voltage / phases	V / Ph	400/3
Mains voltage, permissible Voltage tolerance Voltage min Voltage max	V	376-427
Frequency	Hz	50
Connection power max.	kW	8,0
Electro motor		
Current pickup, full load (after 5 min)	a	<13
Motor protection switch Adjustment valueEinstellwert	a	15
Electric motor speed	rpm	
High-pressure pump oil volume	l	1,1
High-pressure pump oil type	type	SAE 90
Feed pressure water	MPa	23,1
min. feed water volume	l/min	1200
max. feed temperature water	°C	60
High pressure nozzle (US-gpm at 40 psi)	US-gpm	052
Flow rate, full load Pressure water	l/h	900-995
Flow rate, full load Suction water	l/h	890-980
delivery servo press	l/h	430-470
Flow rate, partial load	l/h	
Detergent 1 flow rate Full load	l/h	>40
Working pressure full load Standard gun, new nozzle (Testing manometer)	MPa	
Working pressure partial load (Testing manometer)	MPa	
Safety valve Opn. press. (test. manom.)	MPa	

X		document		number	type	version	status	sheet	of
Technical specificatio				5372673	TDA	02	FR	1	2
Datum date	Gezeichnet drawn by	Geprüft checked by	Normgeprüft std. checked by	Änderung / Engineering change index Anzahl / count			Ersatz für / replaces Datum / date		
2015-06-18	AW03274	-----	-----						
4	3			2	1				

Compliance with the current version of Kärcher standard KN 050.032 Constituent substances (ban of lead, cadmium, etc.) must be guaranteed. Standard date format according to ISO 8601 (YYYY-MM-DD).
 The reproduction, distribution and utilization of this document as well as the communication of its contents to others without explicit authorization is prohibited. Offenders will be held liable for the payment of damages.
 All rights reserved in the event of the grant of a patent, utility model or design. Copyright © Alfred Kärcher GmbH & Co. KG

4	3	2	1									
KÄRCHER [®] Winnenden	Benennung / description HD 10/21-4 S *EU-I HD 10/21-4 S *EU-I		Material-Nr. / material no. 1.286-300.0									
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width: 70%;">Overflow valve open. press. (Testing manometer)</td> <td style="width: 10%; text-align: center;">MPa</td> <td style="width: 20%;"></td> </tr> <tr> <td>Pressure switch 1 (on)</td> <td style="text-align: center;">MPa</td> <td></td> </tr> <tr> <td>Pressure switch 2 (off)</td> <td style="text-align: center;">MPa</td> <td></td> </tr> </table>				Overflow valve open. press. (Testing manometer)	MPa		Pressure switch 1 (on)	MPa		Pressure switch 2 (off)	MPa	
Overflow valve open. press. (Testing manometer)	MPa											
Pressure switch 1 (on)	MPa											
Pressure switch 2 (off)	MPa											
X		document Technical specificatio	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>number</td> <td>type</td> <td>version</td> <td>status</td> </tr> <tr> <td>5372673</td> <td>TDA</td> <td>02</td> <td>FR</td> </tr> </table>	number	type	version	status	5372673	TDA	02	FR	
number	type	version	status									
5372673	TDA	02	FR									
Datum date	Gezeichnet drawn by	Gepreuft checked by	Normgeprüft std. checked by									
2015-06-18	AW03274	-----	-----									
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"></td> <td style="width: 50%;"></td> </tr> </table>				<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"></td> <td style="width: 50%;"></td> </tr> </table>			<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"></td> <td style="width: 50%;"></td> </tr> </table>					
4	3	2	1									

F
E
D
C
B
A