

# RM 752

## Stripping agent

# PRODUCT INFORMATION

**strong alkaline stripping agent - preferable processing with floor scrubber machines -**



### **Properties:**

- \* powerful stripping agent
- \* can be used for the final cleaning of construction sites
- \* usable for manual cleaning
- \* removes shiny, wax and polymer coatings
- \* free of solvents
- \* pH- value approx. 13 in concentrate
- \* green liquid with fresh odour

### **Fields of application:**

- \* offices
- \* shopping centres
- \* shops
- \* plastic floors
- \* final cleaning of construction sites
- \* all water-resistant hard surfaces insensitive to alkalines

### **Processing:**

	<b>dosing</b>	<b>temperature</b>
* maintenance cleaning	1%	up to 60°C
* basic cleaning <sup>1)</sup>	10-50%	up to 60°C
<sup>1)</sup> reaction time approx. 10-15 min.		

Rinse and neutralize with clear water after the basic cleaning

### **Economy**

for the application with floor- scrubber machines: 1 l RM 752 is sufficient for the basic cleaning of approx. 10 m<sup>2</sup>, dosage 25%.

### **Handling:**

at first put water into the tank and then add cleaning agent and mix it; when using large machines, make the predilution separately and then put into the tank.

### **Remarks:**

- \* strong alkaline, therefore use only on alkali- unsensitive surfaces (we recommend pre-tests for material compatibility)
- \* do not allow cleaning agent solutions to dry on the surface.
- \* after basic cleaning wipe with clear water
- \* no application on wood or unsealed parquet
- \* store frost-free

# **RM 752**

Stripping agent

## PRODUCT INFORMATION

### **Attention:**

C Corrosive; R 34 Causes burns

S 1/2 Keep locked up and out of the reach of children.

S 23 Do not breathe spray.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S 45 In case of accident or if you feel unwell, seek medical advice immediately. (Show the label where possible.)

S 51 Use only in well-ventilated areas.

S 60 This material and its container must be disposed of as hazardous waste.

### **Further information:**

\* Material safety data sheet

### **Process:**

object: e.g. PVC floor

\* install the machine (fitting BR-/BD-accessories)

\* make predilution (25%), fill into the tank

\* clean the object

\* neutralize with clear water

**Alternative:** RM 750 Intensive basic cleaner