

Cold water HD 9/16 ST



Overview

Cold water high-pressure cleaner

Order no. 1.374-101.0

Standard accessories

Trigger gun Easy Press, Trigger gun with soft grip, Servo Control, High-pressure hose 10m DN 8, 315 bar, Spray lance 1050mm, Triple nozzle (0°/25°/40°) Manual, Anti-twist system (AVS), Stainless steel spray lance 1050cm, przekręcana lanca spryskująca

Technical data

Quantity of current phase Ph	3
Frequency Hz	50
Voltage V	400
Fuse protection A	Min. 16
Water flow rate l/h	550-900

Description

Solution for exceptional water flow rate. Cleaning can be performed either with cold water or with warm water from a suitable existing source. The maximum permissible water inlet temperature is 70°C. Suitable for direct connection at washing site. A maximum of 6 take-off points is possible. Made of corrosion resistant stainless steel.

Application

Professional high-pressure cleaning is indispensable for the maintenance and care of tools, rooms, outdoor areas and vehicle fleets in industry and the trades. The special advantages of stationary high-pressure cleaning come into their own in all those places where it is necessary to clean to high standards on a regular basis.

Cold water

HD 9/16 ST

Features & Benefits

Water and air-cooled motor housing

Tubular stainless-steel frame
with integral wall mounting bracket

Stainless-steel float tank
for constant water feed, reliably prevents back flow

Switchbox with adjustable timer module (2-8 min.)
to disconnect unit from power supply when it is not in use. Connection for remote control / reset.

Pulsation damper
avoid surges in pressure in the stationary pipework system

Control cable

Control cable 5 x 1.5

Order no. 6.641-061.0



Easy Press Trigger gun

Servopress Controller

Servopress controller
Order no. 4.775-470.0



Easy Press high-pressure gun with soft grip insert

Easy Press trigger gun, integral
Order no. 4.775-463.0



Elementy instalacji wysokociśnieniowych

Quick release coupling, fixed part, R 1/2" internal thread

fixed part
Order no. 6.463-025.0



Cold water

HD 9/16 ST

Quick-release coupling, moveable part, M 22 x 1,5

loose part

Order no. 6.463-023.0

**Angle threaded connection, stainless steel (Ermeto)**

(VA)

Order no. 6.386-466.0

**T-threaded connection, stainless steel (Ermeto)**

Stainless steel

Order no. 6.386-465.0

**Union nut, stainless steel (Ermeto)**

(VA)

Order no. 6.386-428.0

**Union nut, steel zinc coated (Ermeto)**

Alternative: stainless steel 6.386-428

Order no. 6.386-423.0

**Cutting ring, steel zinc coated (Ermeto)**

Order no. 6.386-357.0

**Angle threaded connection, steel zinc coated (Ermeto)**

Alternative: stainless steel 6.386-466

Order no. 6.386-356.0

**T-threaded connection, steel zinc coated (Ermeto)**

Alternativ : stainless steel 6.386-465

Order no. 6.386-269.0



Cold water

HD 9/16 ST

Pipe insulation (Ermeto)

Order no. 6.286-147.0

**Shut-off valve, stainless steel (Ermeto)**

Order no. 4.580-163.0

**Shut-off valve, steel, zincd (Ermeto)**

Alternativ : stainless steel 4.580-163

Order no. 4.580-144.0

**Connector pipe/stop valve, stainless steel (Ermeto)**

Order no. 2.638-183.0

**Connector pipe/stop valve, steel, zincd (Ermeto)**

Alternative: stainless steel 2.638-183

Order no. 2.638-182.0

**Connector pipe/high-pressure hose, stainless steel (Ermeto)**

Stainless steel

Order no. 2.638-181.0

**Connector pipe/high-pressure hose, steel, zincd (Ermeto)**

Alternativ : stainless steel 2.638-181

Order no. 2.638-180.0

**HP-pipe set, stainless steel, 3 m with fixing materials (Ermeto)**

Order no. 2.420-006.0



Cold water

HD 9/16 ST

HP-pipe set, steel, zincd, 3 m with fixing materials (Ermeto)

Alternativ : stainless steel 2.420-006

Order no. 2.420-004.0



High pressure hoses

High-pressure hose, 1.5 m, DN 8, incl. connection pieces

Order no. 6.390-178.0



High-pressure hose 10 m, DN 8, AVS gun connection

With patented AVS connection in trigger gun (pivot mounted) and hand screw union. M22x1.5 with anti-kink protection ID 8/155 °C/315 bar

Order no. 6.390-025.0



Hose track system

Spring tie

Order no. 6.542-001.0



C-rail wall bracket

Order no. 6.541-039.0



C-rail bracket

Order no. 6.541-029.0











C-rail end clamp

Order no. 6.541-028.0



Cold water

HD 9/16 ST

c-rail holder Order no. 6.541-027.0	
C-rail line trolley Order no. 6.541-026.0	
C-rail end stop Order no. 6.541-025.0	
C-rail holder Order no. 6.541-012.0	
C-rail connector Order no. 6.541-011.0	
C-rail section per metre Order no. 6.233-017.0	
Spray lance holder Order no. 4.042-610.0	
Hose reel incl. hp-hose hose 20 m, automatic, open, aluminium fr 20m Order no. 2.637-750.0	

Cold water

HD 9/16 ST

Hose reel incl. hp-hose 10 m, automatic, closed, yellow painted

10m

Order no. 2.637-238.0



Swivelling outrigger 180 °, on pillar (price per bay)

Order no. 2.637-121.0



Pivoting spray lance

Pivoting spray lance

Spray lances in various lengths, stainless steel with hand screw union.

Ergonomically shaped handle mouldings for optimum control and insulation.

Can be turned 360° under pressure.

Order no. 4.760-364.0



Pivoting spray lance

Spray lances in various lengths, stainless steel with hand screw union.

Ergonomically shaped handle mouldings for optimum control and insulation.

Can be turned 360° under pressure.

Order no. 4.760-550.0



Plant installation

Emergency stop switch

Order no. 2.744-002.0



Remote control

Coin acceptor for token 26 x 2,3 with hole

Token

Order no. 6.768-063.0



Cold water

HD 9/16 ST

Coin-operated control

Order no. 2.639-436.0



Remote reset

Order no. 2.637-491.0



Self-winding hose reel for wall mounting

Add-on kit wall fastening hose reel

Add- on kit to fasten a hose reel at the wall.

Order no. 2.639-931.0



Hose reel without hp-hose, automatic

Self-winding hose reel (without HP hose) Kärcher HD hose plug-in system

Order no. 2.639-919.0



Take-off point equipment

Spray lance holder, wall mounted

Order no. 2.042-003.0



Zahlungssysteme

Tokens

Tokens, dia. 26 x 2.3 mm

Order no. 6.768-169.0

