



Overview

Upright cold water high-pressure cleaner. Servopress for adjustment of pressure and water flow rate directly on the trigger gun, pressure switch control, Easy-Press trigger gun with soft grip surface, pivoting stainless steel spray lance, detergent tank, separate compartment for nozzles.

Order no. 1.286-501.0

Standard accessories

Trigger gun Easy Press, Trigger gun with soft grip, High-pressure hose 20m, Spray lance 1050mm, Triple nozzle (0°/25°/40°) Touchless, Dirt Blaster, Integral high-pressure hose, Antitwist system (AVS), Pressure switch control, Stainless steel spray lance 1050mm, Servo Control

Technical data

| Quantity of current phase Ph | 3 |
|--------------------------------|--------------|
| Frequency Hz | 50 |
| Voltage V | 400 |
| Water flow rate I/h | 500-1000 |
| Pressure bar/MPa | 30-250/3-25 |
| Max. Water feed temperature °C | up to 60 |
| Connected load kW | 9,2 |
| Weight kg | 64 |
| Dimensions (L x W x H) mm | 560x500x1090 |
| Detergent tank I | 6 |

Description

The three-phase HD 10/25 S cold water high-pressure cleaner is user friendly and offers an operating pressure of 250 bar at a maximum throughput rate of 1000 l/h.

Thanks to its upright construction, the HD 10/25 S takes up less space than a conventional machine and is much easier to manoeuvre, especially up and down steps and stairs. Its large diameter, rubber-tyred wheels ensure maximum mobility even in difficult terrain. The push handle adjusts to the most comfortable height for the user. Accessories that are not in use can be kept safely in a separate nozzle compartment.

The easy-press trigger gun offers a high degree of user comfort since it requires less effort to hold and operate and features a servopress controller for convenient adjustment of pressure and water flow rate. The spray lance can be pivoted through 360° while operating at full pressure.



...

Other features are the pressure switch control, which turns off the pump as soon as the trigger is released and thus extends the service life of the motor and pump, and the electronic monitoring system for the motor and pump unit. The built-in detergent tank has a capacity of 6 litres.

The HD 10/25 S has been designed for tough daily operating conditions. The chemical-resistant brass cylinder head and stainless steel pistons with ceramic sleeves are combined with an efficient air-water cooling system to guarantee a long service life.

Application

On farms or building sites Removes heavy soiling quickly, thoroughly and economically while providing exceptional operator comfort

Features & Benefits

 $0^{\circ}/25^{\circ}/40^{\circ}$ triple nozzle with touchless changeover Quick changeover from high-pressure pencil jet to 25° high-pressure fan jet, manual changeover to 40° fan jet for detergent intake and application in low-pressure mode.

6-litre detergent tank with infinitely variable metering valve and additional nozzle compartment Detergent available anywhere at any time, economic consumption as a result of precise metering, triple nozzle or Dirt Blaster safely accommodated on machine

Brass cylinder head with stainless steel inlet and pressure valves and safety valve High grade materials for a long service life, machine is protected against overload

Detergent injector Detergent applied in low-pressure mode by simply changing setting on triple nozzle

Easy Press Trigger Gun can be held and operated with greatly reduced effort

Electronic motor protection system with LED display Leakage, over/undervoltage and other operating conditions are monitored and indicated and the machine is shut down automatically in the event of a fault.

Endurance tested, 4-pole three-phase motor (1400 rpm) with a combination of air and water cooling and motor protection switch

Powerful drive unit with optimized motor cooling and overload cut-out, good intake performance, long life

Large rubber tyred wheels and support stand with rubber buffer



> ...

Excellent mobility even on rough surfaces and up and down steps, rock steady in operating position

Oil inspection glass in machine cover Pump oil level can be checked quickly and easily

One-piece motor/pump housing Very quiet, compact construction

Pressure switch control Direct on/off control via trigger gun, exceptional reliability, extended pump life

Removable machine cover made of impact resistant, recyclable polypropylene

Adapter für Druckregelstrahlrohr

Adapter for variable pressure spray lance For items 9, 10, for mounting accessories to lance, M 24/18 x 1.5 Order no. 4.762-075.0

Boron carbide nozzle

Boron carbide nozzle

(In addition to nozzle packs. Very wear-resistant nozzle for continuous-duty operation.) Order no. 6.415-084.0

ø

Ø

Crane lifting kit

Crane lifting kit Effortless handling by crane. Order no. 2.640-438.0

ø

Dirt Blaster, changeover

Dirt Blaster, changeover

changeover to high-pressure fan jet Order no. 4.763-957.0



Dirt Blaster, changeover

Changeover to chemical intake (low pressure) Order no. 4.763-949.0

Dirt Blaster, not adjustable

Dirt Blaster, without changeover

Rotating pencil jet for maximum dirt removing power. Order no. 4.763-250.0

Easy Foam Set

Easy Foam Set

Complete, ready-to-use HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. Order no. 2.640-693.0

Easy Press Trigger gun

Servopress Controller Servopress controller Order no. 4.775-470.0

Easy Press high-pressure gun with soft grip insert Easy Press trigger gun, integral Order no. 4.775-463.0

Fine mesh water filter

Fine mesh water filter Mounted to machine inlet, 80 øm Order no. 4.730-102.0





Ø



Mounts to machine inlet 150 øm

Flächenreiniger FR 30 ME

Surface cleaner, 300 mm diameter

bearings. Integral vacuum connection.

Fine mesh water filter

Order no. 2.638-270.0

Order no. 2.640-355.0

© 2007 Alfred Kärcher GmbH & Co. KG

High-pressure hose, 20 m, DN 8, PN 160 bar, AVS gun

High pressure hoses

connectionm,

Food industry version, AVS connection in trigger gun grey ID 8/155°C/160 bar Order no. 6.390-705.0

Foam nozzle mounting kit

Anbausatz Schaumdüse

For applying foam detergent in metered quantities in sanitary and food areas, or where long reaction time is necessary, mounts to spray lance in place of HP nozzle Order no. 2.637-926.0

A rotating nozzle beam with Kärcher Power nozzles has an area coverage up to 10 times larger than conventional methods. Stainless steel version. Ceramic

Geka coupling

Geka coupling with female thread Order no. 6.388-458.0

Geka coupling

with hose liner Order no. 6.388-455.0









Ø

Ø



| High-pressure hose, 10 m, DN 8, PN 160 bar, AVS gun connectionm, | |
|--|---|
| Food industry version, AVS connection in trigger gun grey ID 8/155°C/160 bar Order no. 6.390-704.0 | |
| High-pressure hose 20 m, DN 8, AVS gun connection Longlife 400 with patented AVS connection in trigger gun (pivot mounted) ID 8/155°C/400 bar Order no. 6.390-208.0 | |
| High-pressure hose 15 m, DN 8, AVS gun connection With patented AVS connection in trigger gun (pivot mounted) and hand screw union. M22x1.5 with anti-kink protection ID 8/155°C/315 bar Order no. 6.390-185.0 | |
| High-pressure hose 20 m, DN 8, AVS gun connection With patented AVS connection in trigger gun (pivot mounted) and hand screw union. M22x1.5 with anti-kink protection ID 8/155 °C/315 bar Order no. 6.390-171.0 | |
| High-pressure hose 20 m, DN 8, PN 200 bar | |
| With M 22x1.5 union at both ends and anti-kink protection ID 8/155°C/315 bar Order no. 6.390-031.0 | |
| | Ø |
| High-pressure hose 20 m, DN 10, PN 400 bar, Longlife, extension Longlife 400, With rotary coupling 2 x M22 x 1.5, ID 8/155°C/400 bar Order no. 6.390-027.0 | |
| High-pressure hose 10 m, DN 10, PN 400 bar, Longlife, extension Longlife 400, Without rotary coupling 2 x M22 x 1.5, ID 8/155°C/400 bar Order no. 6.390-026.0 | |



| With M 22x1.5 union at both ends and anti-kink protection ID 10/155 °C/220 bar | |
|--|---|
| Order no. 6.390-023.0 | Ţ |
| High-pressure hose, 15 m, DN 8, 315 bar, extension With M 22x1.5 union at both ends and anti-kink protection ID 8/155 °C/315 bar Order no. 6.390-010.0 | |
| | ø |
| High-pressure hose 10 m, DN 8, PN 315 bar, extension With M 22x1.5 union at both ends and anti-kink protection ID 8/155°C/315 bar Order no. 6.389-891.0 | |
| | ø |
| High-pressure hose, 20 m, DN 8, PN 180 bar, food version, extension Food industry version with M 22x1.5 union at both ends, anti-kink protection, ID 8, with rotary coupling, for food industry, up to 230 bar Order no. 6.389-581.0 | |
| High-pressure hose, 10 m, DN 8, extension, food version Food industry version with M 22x1.5 union at both ends, anti-kink protection, ID 8, with rotary coupling, for food industry, up to 230 bar Order no. 6.389-479.0 | |
| High-pressure hose, 10 m, DN 8, incl. swivelling joint Longlife 400, With rotary coupling 2 x M22 x 1.5, ID 8/155°C/400 bar Order no. 6.388-083.0 | |
| High-pressure hose 10 m, DN 8, AVS gun connection With patented AVS connection in trigger gun (pivot mounted) and hand screw union. M22x1.5 with anti-kink protection ID 8/155 °C/315 bar Order no. 6.390-025.0 | |



High-pressure hose 10 m, DN 8, AVS gun connection, longlife

Longlife 400 with patented AVS connection in trigger gun (pivot mounted) ID 8/155 °C/400 bar Order no. 6.389-856.0

Inno Foam Set

Inno Foam Set

Complete, ready-to-use HP foam system for use with mobile and stationary HD/HDS units for cleaning and disinfection. Twin spray lance with foam nozzle and changeover to HP jet for clear rinsing etc., HP chemical injector with precision 0-5% metering valve. Order no. 2.640-692.0

Installationsmaterial

Rotating joint

Reliably prvents HP hose twisting. M 22x1.5 connection with protector Order no. 4.401-076.0

Kugeldüsenträger

Rollover nozzle holder

Changes from solid to fan jet with flick of the wrist. Knurled nut for changeover to low pressure chemical intake, without nozzles (order Kärcher Power nozzle separately) Order no. 4.764-012.0



Ø

Kupplung

Double pipe union For connecting and extending HP hoses. 2 x M22 x 1,5 connections, brass with rubber protector Order no. 4.403-002.0





Machine-specific nozzle kit

| Machine-specific nozzle kit detergent injector + HP nozzle + union Order no. 4.769-048.0 | |
|--|----|
| Power nozzle with union for item 2.838-821 and 2.640-355 Order no. 2.640-442.0 | |
| | ø |
| Nemle kit for UKE 50 enrow head | |
| Nozzle kit for HKF 50 spray head | |
| HKF 50 spray head Nozzle kit for items 3.631-039 and 3.631-009. 1 nozzle Order no. 6.415-447.0 | |
| | ø |
| HKF 50 spray head Nozzle kit for items 3.631-039 and 3.631-009. 2 nozzle Order no. 6.415-446.0 | |
| | Ţ |
| Screw plug Screw plug. For operating spray head with one nozzle Order no. 5.411-061.0 | |
| | ø |
| Double handle Cone for installing unit in bungholes. Double handle, for exact control of spray head. | |
| Order no. 4.132-002.0 | ,ø |
| Double handle Cone for installing unit in bungholes. Double handle, for exact control of spray head | |
| Order no. 2.863-036.0 | ø |



Nozzle kits for Inno/Easy Set

Nozzle kits for Inno/Easy Set

Ideally match performance to different machine outputs for economic operation. Order no. 2.640-694.0

ø

Ø

Ø

181

Nozzle pack for wet-blasting attachment

Nozzle pack for wet-blasting attachment

Consisting of wet-blasting nozzle and nozzle insert, only for use with wetblasting attachment 4762-010/-022 Order no. 2.637-902.0

Pipe cleaning nozzle

Pipe cleaning nozzle

With female thread, different spraying directions for environment-friendly cleaning of blocked drains and pipes.Nozzle orifices are positioned so that nozzle pulls itself and the hose into the pipeBrass, for M22 x 1.5 connection directly to HP hose Order no. 5.763-013.0

Pipe cleaning nozzle

With female thread, different spraying directions for environment-friendly cleaning of blocked drains and pipes.Nozzle orifices are positioned so that nozzle pulls itself and the hose into the pipe Brass, for M22 x 1.5 connection directly to HP hose Order no. 5.763-012.0

Pivoting spray lancer

Pivoting spray lancer

Spray lances in various lenghts, stainless steel with hand screw union. Ergonomically shaped handle mouldings for optimum control and insulaton. Can be turned 360° under pressure. Order no. 4.760-386.0



Spray lance, 2040 mm, rotatable Spray lances in various lenghts, stainless steel with hand screw union. Ergonomically shaped handle mouldings for optimum control and insulaton. Can be turned 360° under pressure. Order no. 4.760-366.0 Spray lance, 1500 mm, rotatable Spray lances in various lenghts, stainless steel with hand screw union. Ergonomically shaped handle mouldings for optimum control and insulaton. Can be turned 360° under pressure. Order no. 4.760-365.0 **Pivoting spray lance** Spray lances in various lenghts, stainless steel with hand screw union. Ergonomically shaped handle mouldings for optimum control and insulaton. Can be turned 360° under pressure. Order no. 4.760-364.0 **Pivoting spray lancer** Spray lances in various lenghts, stainless steel with hand screw union. Ergonomically shaped handle mouldings for optimum control and insulaton. Can be turned 360° under pressure. Order no. 4.760-550.0 Ø

Rotary washing brush

Rotary washing brush

Driven by water jet. Gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 85 °C. M 18 x 1.5. (replaceable brush element) Order no. 4.762-287.0

Rotary washing brush

Driven by water jet. Gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 85 °C. M 18 x 1.5. (replaceable brush element) Order no. 4.762-283.0

© 2007 Alfred Kärcher GmbH & Co. KG

Cold water super class HD 10/25-4 SX Plus

Self-winding hose reel for wall mounting

Add-on kit wall fastening hose reel

Add- on kit to fasten a hose reel at the wall. Order no. 2.639-931.0

Hose reel without hp-hose, automatic

Self-winding hose reel (without HP hose) Kärcher HD hose plug-in system Order no. 2.639-919.0

Spray lance

Spray lance, 250 mm, fixed Stainless steel with hand screw union, does not pivot In conjunction with extended trigger aun Order no. 4.760-058.0

Spritzkopf HKF 50, Messing

HKF 50 spray head, brass

Reach 850 mm. Interior cleaning head for drums, barrels and tanks. For bungholes of 50 mm and more. Connects directly to high-pressure cleaner. Driven by electric motor. Operates in vertical and horizontal positions. Order no. 3.631-039.0

Suction filter

Suction filter

With/without non-return valve, brass Order no. 4.730-019.0

Suction filter

With/without non-return valve, brass Order no. 4.730-012.0









Ø

Ø



Triple nozzle, touchless changeover

Triple nozzle, touchless changeover

Fast and easy jet changeover by flicking the nozzle. Choose from highpressure pencil jet, high-pressure fan jet and low-pressure fan jet. On machines with injector, the low-pressure is used for picking up and applying detergent. M18 x 1.5 connection. Order no. 4.767-065.0

Unterbodenstrahlrohr

Underbody lance Mobile. For effective and convenient cleaning of underbodies and wheel arches. Stainless steel. Without HP nozzle Order no. 4.760-245.0

Variable pressure spray lance

Variable pressure spray lance

With integral pressure gauge for infinitely variable pressure control directly on lance. Nozzle connection M 24 x 1.5. Chemical feed in low pressure mode. Variable pressure lance and Kärcher Power nozzle. Order no. 4.760-362.0

Variable pressure spray lance

With integral pressure gauge for infinitely variable pressure control directly on lance. Nozzle connection M 24 x 1.5. Chemical feed in low pressure mode. Variable pressure lance and Kärcher Power nozzle. Order no. 4.760-230.0

Vario nozzle 0°-90°

Vario nozzle 0-90°

High-pressure jet infinitely variable between 0° and 90° so it can be exactly matched to all types of soiling and surfaces. Order no. 4.763-039.0















Verbindungsstück

Adapter

For connecting HP nozzles and accessories directly to trigger gun (with nozzle union) $1 \times M22 \times 1.5/1 \times M18 \times 1.5$ Order no. 4.402-022.0

Ø

Ø

Ø

Ø

Water supply hose

Water supply hose ID 19 R1"/R1" - up to 85°C Order no. 4.440-270.0

Water supply hose

ID 19 R1"/R 3/4" - up to 85°C - for suction mode Order no. 4.440-207.0

WC-Strahlrohr

WC-Spray lance With nozzle. Specially shaped for cleaning WCs. Stainless steel. Order no. 4.760-073.0

Wet blasting attachment

Wet-blasting attachment (without nozzles) Adds abrasive to high-pressure jet. For removing paint, rust, scale. Mounts to spray lance in place of HP nozzle. Without abrasive flow control Order no. 4.762-022.0

Wet blasting attachment (without nozzles)

Adds abrasive to high-pressure jet. For removing paint, rust, scale. Mounts to spray lance in place of HP nozzle. With abrasive flow control Order no. 4.762-010.0