K 5.80 M plus upright, compact, with strong performance





Water flow rate:	450 l/h
Pressure:	20-125 bar
Max. water feed temperature:	40 °C
Connected load 230 V/1~/50 Hz:	2.1 kW
Power supply:	10 A
Weight:	15 kg
Dimensions LxWxH:	396x35 <mark>4x899 mm</mark>
Order number:	1.396-300







- Modern design, upright construction with handle and wheels
 - High mobility, even over steps and stairs, classification system for all the accessories

Functionality:

Accessories can be conveniently stowed in the machine cover and on the handle.

Trigger gun is kept in a holster on the side of the machine.

9m high-pressure hose for wide range of action.







- Large ergonomic handle with cable hook
- Secure stowing of power cable

- Totally enclosed by high-impact plastic cover
 - Protection from dirt and damage, corrosion-resistant, impact-resistant, recycable







- Water connection (1) with filter and Gardenascrew top
 - Connect water hose without problem, pump protection
- High pressure connection (2) of aluminium
 - Comfortable connecting of high-pressure hose
- Large on/off-switch
 - Easy to handle









- Air cooled **2.1 kW**-asynchronous motor (2800 R/min)
 - Powerful drive
- Three piston pump (axial) made of aluminium
 - Matured pump technology, optimum efficiency, maintenance-free, long service life
- **Polyfiber** cylinder head with inlet and pressure valves made of high-grade plastic
 - Corrosion-resistant, low weight, formstable







Pressure switch control

Machine stops when gun is closed, relieves high pressure system and motor

Detergent injector

Detergent is applied in low pressure with the variopower spray lance

TÜV-/GS-tested

High security and quality standard



K 5.80 M plus Standard Accessories







High-pressure hose with protective rubber sleeve, pivoted trigger gun

Ergonomic gun design

Enhances operator comfort, fatigue-free working, stowing of the power cable

Variopower spray lance



For every cleaning task the right power

Dirt blaster

Universal professional cleaning tabs RM 555

