



IVR 40/30 Pf

The IVR 40/30 Pf industrial vacuum: with high-quality side channel blower and pocket filter. Ideal for long operating cycles and fine dust in the production area and around production machinery.



- 1 Robust material and a design suitable for industrial purposes
- Ideal for use in the metals processing industry.

2 Pleasant operating noise

Sound absorbers on the air outlet pipes make for a comfortable operating noise with high suction power.

- 3 Cyclone-like pre-separation system
- Protects the filter and increases its working time. This saves on costs and increases versatility.

4 Highly efficient IE2 motor for higher suction power

With a comparable input power, the efficient IE 2 motor delivers more suction power than traditional motors.

IVR 40/30 Pf

Cyclone-like pre-separation system

- Sound reduction
- Safe accessory storage

Technical data		
Order no.		9.986-067.0
EAN code		4054278030081
Rated input power during operation	kW	3
Air flow rate	l/s / m³/h	87.5 / 315
Vacuum	mbar / kPa	260 / 26
Container capacity	I	40
Filter area	m²	1.75
Main filter dust class		M
Sound pressure level	dB(A)	60
Nominal diameter of connection		ID 72
Weight	kg	128
Nominal diameter of accessory		ID 72 / ID 52
Dimensions (L × W × H)	mm	890 × 670 × 1560
Equipment		
A second sector second set della second		

Accessories in scope of delivery	No
Container in scope of delivery	40 I
Filter cleaning	Manual



		Order no.	Quantity	ID	Length / width	Price	Description	
Adapters and spare parts			1					
Vacuum connector, 90°	1	9.981-313.0	1 piece(s)	ID 72			90° connector for IVR vacuums with connection adapter ID	ŀ
							72 and hook for hose attachment, rotatable by 360°.	+
Hose connection	2	9.981-261.0	1 piece(s)	ID 52			For attachment to hose ID 52, with slit and hook for hose attachment.	[
	3	9.981-145.0	1 piece(s)	ID 72			Hose connection piece with hooks and internal cone ID 70.	[
Accessories connection	4	9.981-325.0	1 piece(s)	ID 52			Rotatable, for attachment to hose ID 52, inner taper for	
			- p(.)				attaching accessories.	[
Y-adapter ID 52 to 2 × ID 42	5	9.981-149.0	1 piece(s)	ID 52			Hose pipe ID 50/40/40; external cone ID 50 on 2 \times internal cone ID 40.	[
Filters and waste disposal bags			1					
Pocket filter	6	9.981-681.0	1 piece(s)		490 mm		Pocket filter, 1.75 m ² , antistatic, dust filter class M.	
Bend, coated								
Bend, screw connection	7	6.902-201.0	1 piece(s)	ID 52			Bend, powder-coated steel, electrically conductive, with stal screw.	۲
	8	6.902-203.0	1 piece(s)	ID 72			Bend, coated, electrically conductive, ID 72; without tap adapters.	[
Suction tube, coated								
Suction tube, screw connection	9	6.902-181.0	1 piece(s)	ID 52	850 mm		For floor cleaning in combination with bend (6.902-201.0) and DN 52 floor nozzles.	[
	10	9.981-910.0	1 piece(s)	ID 72	750 mm		Suction tube ID 72, tube length ID 750 mm. For connection with hose and bend ID 72 (6.902-203.0).	[
Floor nozzles								
Multi-purpose floor nozzle, wet/	11	6.902-184.0	1 piece(s)	ID 52	370 mm		Multi-purpose nozzle, width 370mm, DN 52	E
dry	12	6.902-186.0	1 piece(s)	ID 52	500 mm		Multi-purpose nozzle, width 500mm, DN 52	[
Brush strip	13	6.903-067.0	2 -part		500 mm		Brush strip for multi-purpose nozzle 500 mm 6.902-186.0.	[
Other nozzles		1	1	1			1	
Flexible nozzle, plastic		6.902-196.0	1 piece(s)	ID 52	250 mm		Nozzle, elastic, rubber, DN 52	
		6.902-198.0	1 piece(s)	ID 72	260 mm		Nozzle, elastic, rubber, DN 72	1
Elongated round nozzle, rubber	16		1 piece(s)	ID 52	315 mm		Suction nozzle, rubber, round, DN 52, length 315mm	[
Round brush, angled	17		1 piece(s)	ID 52			Suction brush, round 45°, DN 52	[
Surface nozzle, aluminium	18	6.902-187.0	1 piece(s)	ID 52	150 mm		Surface nozzle, aluminium, width 150mm, DN 52	[
Crevice tools	10	6.902-194.0	1 piece(s)	ID 52	340 ×	1	Cravice people plastice long DN 52 width 12mm	T
Crevice nozzle, plastic					13 mm		Crevice nozzle, plastics, long, DN 52, width 13mm	[
Crevice nozzle, plastic, flexible	20	6.902-211.0	1 piece(s)	ID 52	425 × 20 mm		Bendable crevice nozzle (ID 52) of plastic for flexible appli- cations, with a nozzle width of 20 mm.	
Crevice nozzle, galvanised	21	6.902-189.0	1 piece(s)	ID 52	350 × 17 mm		Crevice nozzle, zinc-plated, width 25mm, DN 52	[
	22	6.902-191.0	1 piece(s)	ID 72	350 × 30 mm		Crevice nozzle, zinc-plated, width 30mm, DN 72	[
Crevice nozzle, lightweight plastic	23	9.988-117.0	1 piece(s)	ID 52			Multi-purpose crevice nozzle, plastic, DN 52.	[
PVC hoses								ſ
Suction hose, PVC, screw connec-	24	6.907-294.0	1 piece(s)	ID 52	3 m		Electrically conductive, accessory end rotary coupling, DN	
tion	25		1 piece(s)	ID 52	5 m		72 vacuum connector	
	26	6.907-296.0	1 piece(s)	ID 72	3 m		Electrically conductive, accessory end rotary coupling, DN	L
	27	6.907-297.0	1 piece(s)	ID 72	5 m		72 vacuum connector (also suitable for use as an extension hose)	
Connection hose, PVC, screw con-	28	6.907-312.0	1 piece(s)	ID 52	3 m		Electrically conductive, accessory end rotary coupling, hose	1
nection		6.907-313.0	1 piece(s)	ID 52	5 m		with DN 52 connector at both ends	

 \blacksquare Included in the scope of supply. $\hfill\square$ Available accessories.

ACCESSORIES FOR IVR 40/30 PF 9.986-067.0

KARCHER

30-31	32-35	36-41	42-43	44-45	46-51	52
53	54	55	56-57	58-59		

		Order no.	Quantity	ID	Length / width	Price	Description	
Suction hose, available by the metre, PVC, screw connection	30	9.980-646.0		ID 52			Electrically conductive, without connections, whole metres up to max. 15 m, price per metre, max. temperature 85 °C, for fine and light suction waste.	
	31	9.980-677.0		ID 72			Electrically conductive, without connections, whole metres up to max. 15 m, price per metre, max. temperature 85°C, for fine and light suction waste.	
EVA hoses								
Suction hose EVA, screw connec-	32	9.988-094.0	1 piece(s)	ID 52	3 m		EVA material, electrically conductive, DN 72 machine con-	
tion	33	9.988-095.0	1 piece(s)	ID 52	5 m		nection with star screw, slit and DN 52 accessory end hinge highly flexible, for fine and light suction waste.	^{2,}
Connection hose EVA, screw con-	34	9.988-090.0	1 piece(s)	ID 52	3 m		EVA material, electrically conductive, DN 52 connection at	
nection	35	9.988-091.0	1 piece(s)	ID 52	5 m		both ends, slit and accessory end hinge, highly flexible, for fine and light suction waste. IVC only as an extension hose, IVR only with reduction.	
PU hoses								
Suction hose, PU, screw connection		6.907-300.0	1 piece(s)	ID 52	3 m		Electrically conductive, accessory end rotary coupling, DN	
	37	6.907-301.0	1 piece(s)	ID 52	5 m		72 vacuum connector	
	38	6.907-302.0	1 piece(s)	ID 72	3 m		Electrically conductive, accessory end rotary coupling, DN	
	39	6.907-303.0	1 piece(s)	ID 72	5 m		72 vacuum connector (also suitable for use as an extension hose)	
Connection hose, PU, screw con-	40	6.907-316.0	1 piece(s)	ID 52	3 m		Electrically conductive, accessory end rotary coupling, hose	
nection	41	6.907-317.0	1 piece(s)	ID 52	5 m		with DN 52 connector at both ends	
Suction hose, available by the	42	9.980-649.0		ID 52			Electrically conductive, without connections, whole metres	
metre, PU, screw connection	43	9.980-650.0		ID 72			up to max. 15 m, price per metre, max. temperature 80 °C, for liquids and abrasive solids.	
Suction hose, available by the metre, light PU, screw connection	44	9.980-680.0		ID 52			Suction hose available in bulk, lightweight, PU (max. 15 m), ID 50, without tap adapters.	
	45	9.980-681.0		ID 72			Electrically conductive, without connections, whole metres up to max. 15 m, price per metre, max. temperature 80 °C, for liquids and solids.	
Metal hoses								
Suction hose, ME-PU, screw con-	46	6.907-306.0	1 piece(s)	ID 52	3 m		Electrically conductive, accessory end rotary coupling, DN	
nection	47	6.907-307.0	1 piece(s)	ID 52	5 m		72 vacuum connector	
	48	6.907-308.0	1 piece(s)	ID 72	3 m		Electrically conductive, accessory end rotary coupling, DN	
	49	6.907-309.0	1 piece(s)	ID 72	5 m		72 vacuum connector (also suitable for use as an extension hose)	
Connection hose, ME-PU, screw	50	6.907-320.0	1 piece(s)	ID 52	3 m		Electrically conductive, accessory end rotary coupling, hose	
connection	51	6.907-321.0	1 piece(s)	ID 52	5 m		with DN 52 connector at both ends	
Suction hose, available by the metre, ME-PU, screw connection	52	9.980-707.0		ID 52			Electrically conductive, without connections, whole metres up to max. 15 m, price per metre, max. temperature 110 °C, for metal shavings with liquids.	
Adapters and spare parts								
Adapter IVC/IVR to ID 61	53	6.902-001.0	1 piece(s)	ID 61			For using IV accessories on IVC and IVR.	
Reducer, ID 72 to ID 52	54	6.902-180.0	1 piece(s)	ID 72			Reduction piece from ID 72 to ID 52.	
Vacuum connector, ID 72 to ID 52.	55	6.902-177.0	1 piece(s)	ID 72			For attachment to suction nozzle and reduction to hoses DN 52	
Hose connection	56	6.902-168.0	1 piece(s)	ID 52			For attachment to hose DN 52	
	57	6.902-173.0	1 piece(s)	ID 72			For attachment to hose DN 72	
Hose connection, rotatable	58	6.902-169.0	1 piece(s)	ID 52			Rotatable, for attachment to hose DN 52	
	59	6.902-175.0	1 piece(s)	ID 72			For attachment to hose DN 72	

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR IVR 40/30 PF 9.986-067.0

60-61 62-	63			65 72		66		$ \begin{array}{c} $	
		Order no.	Quantity	ID	Length / width		Price	Description	
Hose clamp	60	6.902-167.0	1 piece(s)	ID 42				For attaching hose to accessory connection DN 42/52	
	61	6.902-176.0	1 piece(s)	ID 72				For attaching accessory connection to hose DN 72	
Hose sleeve	62	6.902-166.0	1 piece(s)	ID 52				For attaching hose to accessory connection DN 52	
	63	6.902-174.0	1 piece(s)	ID 72				For attaching accessory connection to hose DN 72	
Star grip M 8	64	6.303-554.0	1 piece(s)	ID 52				Star grip M 8 as replacement for all bends and DN 52/72 tap adaptors.	
Y connector DN 72 to 2 × DN 5	2 65	6.902-206.0	1 piece(s)	ID 72				Junction for machine connection DN 72 to two DN 52 con- nections.	
Suction container and swarf ba	skets								
Pre-separator cover for 200 l drum	66	9.986-371.0	1 piece(s)	ID 52				Pre-separator cover for 200 I standard drum with ball float for overfill prevention. Screw connection DN 52.	
	67	9.986-370.0	1 piece(s)	ID 52				Pre-separator cover for 200 l standard drum. Screw connection ID 52.	

	67	9.986-370.0	1 piece(s)	ID 52		Pre-separator cover for 200 I standard drum. Screw connec- tion ID 52.
Pre-separator, 125 l, complete	68	9.986-372.0	1 piece(s)	ID 52		Pre-separator, coated, complete with cover, DN 52 connec- tions, ball float for overfill prevention, 125 I container and tilting chassis.
Drum separator	69	9.982-081.0	1 piece(s)	ID 52		Filling device with ID 52 connections, screw connection, for filling of e.g. 200 I drums via the bunghole.
Filters and waste disposal bags						
Disposal bags, paper	70	6.904-346.0	10 piece(s)			Disposal sack, paper, 60 I for dust-free disposal
Disposal bags, PE	71	6.907-347.0	5 piece(s)			Disposal bag, PE, 5 pcs, 50 l, for low-dust disposal of suction waste.
Accessory kits IVC, IVS, IVR (3 phase	es)					
Vacuuming kit for solids/small quantities of liquids, screw con- nection	72	2.869-108.0	6 -part	ID 52		3 m ME-PU suction hose ID 52 (6.907-306.0), bend ID 52 (6.902-201.0), 850 mm suction tube ID 52 (6.902-181.0), 370 mm floor tool ID 52 (6.902-184.0), nozzle, flexible ID 52 (6.902-196.0), 150 mm aluminium surface nozzle ID 52 (6.902-187.0).
Vacuuming kit for dry/coarse particles, screw connection	73	2.869-109.0	6 -part	ID 52		3 m PU suction hose ID 52 (6.907-300.0), bend ID 52 (6.902-201.0), 850 mm suction tube ID 52 (6.902-181.0), 370 mm floor tool ID 52 (6.902-184.0), nozzle, flexible ID 52 (6.902-196.0), 150 mm aluminium surface nozzle ID 52 (6.902-187.0).
Bend					· · ·	
Bend with hook, screw connection	74	9.981-320.0	1 piece(s)	ID 52		Bend, powder-coated steel, electrically conductive, with star grip and hook for hanging hose.
Suction nozzles						
Vacuum brush	75	9.981-912.0	1 piece(s)	ID 52	300 mm	Vacuum brush, 300 mm, with 45° connection, with star screw, horsehair bristles.
Crevice nozzle, zinc coated, flexi- ble	76	9.981-425.0	1 piece(s)	ID 52	490 × 20 mm	Crevice nozzle, steel, zinc coated, flexible, slit width 20 mm.
Nozzle, zinc coated, flexible, with rubber tip	77	9.981-421.0	1 piece(s)	ID 52	30 mm	Round nozzle, steel, zinc coated, flexible, with rubber tip DN 30.
Miscellaneous						
Cable drum with 25 m cable	78	9.982-080.0	1 piece(s)			AC cable drum with 25 m cable, for fixing in accessories holder 6.645-412.0.

■ Included in the scope of supply. □ Available accessories.