

## Heated high pressure cleaner three phase

## **HDS 695-4 M ECO \*EUR**

Hot water high-pressure cleaner from the medium-duty class with a max pressure of 150 bar. New generation of heavy-duty machines combines innovative engineering with a max of user convenience, economy and a long service life. The unit has a three-piston axial-pump with ceramic sleeves (1400 rpm) and a 4-pole, water-cooled electric motor.

## Standard accessory:

- 10 m longlife high pressure hose
- Easy Press trigger gun with soft grip inlay and Servo Control
- pivoting stainless steel spray lance (1050 mm)
- power nozzle
- integral fuel (25 I) and detergent tank (20 I)
- flue gas temperature limiter
- SDS system (Soft damping system)
- fine mesh water filter
- ceramic pistons



Order no. 1.025-315 EAN-code 4039784055377

Pallet size 1 unit

## **Technical Data**

NA/atau flavorata	400.000	L/In
Water flow rate	400-800	l/h
Pressure	30-150	bar
Water feed temperature (max.)	155 / 80	°C
Connected load	6.4	kW
Consumption, fuel oil	5.2	kg/h
Power supply	3 / 400 / 50	~ / V / Hz
Weight (without accessory)	117	kg
Dimensons (L x B x H)	1285 x 690 x 835	mm
Packing weight	168	kg
Packing dimensions (L x B x H)	1200 x 750 x 1050	mm