



#### **Standard accessories**

Trigger gun Easy Press, Trigger gun with soft grip, High-pressure hose 15m, Spray lance 850mm, Triple nozzle/Power nozzle Manual, Triple nozzle (0°/25°/40°) Manual, Dirt Blaster, Integral high-pressure hose, Anti-twist system (AVS), Pressure switch control, Stainless steel spray lance 850mm, Servo Control

### **Overview**

Cold-water high-pressure cleaner with robust 4-pole low-speed three-phase motor.

Order no. 1.524-211.0

### **Technical data**

Quantity of current phase Ph	3
Frequency Hz	50
Voltage V	400
Water flow rate I/h	240-700
Pressure bar/MPa	10-180/1-18
Max. Water feed temperature °C	up to 60
Connected load kW	5
Weight kg	45,3
Dimensions (L x W x H) mm	467x407x1010

#### **Description**

Powerful high-pressure cleaner with 4-pole low-speed three phase motor. The cleaner comes with AVS, the patented anti-twist system for easy and safe operation, a rugged 3-piston axial pump with provides a long service life and Kärcher's automatic pressure-controlled shutdown for low energy consumption.

Water flow rate and pressure can be infinitely varied by rotating the Servo Control on the trigger gun. The new Easy Press trigger gun can be held and operated with greatly reduced effort. The sturdy push handle (aluminium) on wich the accessories can be accommodated provides good manoeuvrability.

Innovative metering and detergent system Switch-Chem for long periods of uninterrupted operation. Equipped with two 2.5-litre bottles, the area coverage can be either doubled or two cleaning agents can be carried for a simple changeover from one to the other without having to stop work.



### **Application**

Ideal for facade or contract cleaning, building sites, agricultural and forestry operations or municipal maintenance services

### Features & Benefits

4-pole air-cooled elecric motor long service life

Easy Press trigger gun can be held and operated with greatly reduced effort

Pressure hose reel, supported at both sides keeps pressure hose tidy, its length ensures a wide working radius

Servo-Control precise adjustment of pressure and water flow rate

Switch CHEM System

Two-way metering valve for precise and infinitely variable control of the detergent feed. Double detergent tank for long periods of uniterrupted operation. Available with optional 2.5-litre quick-change tank system.

Three-piston axial pump with hardened stainless steel pistons, swash-plate drive system Direct drive with minimum moving parts, optimum efficiency, long service life

Vertical construction for high mobility and superior manouverability by less space to store the unit

### Absperrhahn

## Shut-off cock

Order no. 4.580-160.0

ø

## Adapter für Druckregelstrahlrohr

Adapter for variable pressure spray lance For items 9, 10, for mounting accessories to lance, M 24/18 x 1.5 Order no. 4.762-075.0

ø



### Boron carbide nozzle

### Boron carbide nozzle

(In addition to nozzle packs. Very wear-resistant nozzle for continuous-duty operation.) Order no. 6.415-084.0

**Dirt Blaster, changeover** 

Dirt Blaster, changeover changeover to high-pressure fan jet Order no. 4.763-957.0

## **Dirt Blaster, changeover**

Changeover to chemical intake (low pressure). Order no. 4,763-951.0

# Easy Foam Set

**Easy Foam Set** Complete, ready-to-use HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. Order no. 2.640-691.0

## Easy Press Trigger gun

# Easy Press high-pressure gun with soft grip insert

Easy Press trigger gun, integral Order no. 4.775-463.0

## Fine mesh water filter

### Fine mesh water filter

Mounted to machine inlet, 80 øm Order no. 4.730-102.0













# Flächenreiniger FR 30 ME

# Surface cleaner, 300 mm diameter

A rotating nozzle beam with Kärcher Power nozzles has an area coverage up to 10 times larger than conventional methods. Stainless steel version. Ceramic bearings. Integral vacuum connection. Order no. 2.640-355.0

# Foam nozzle mounting kit

# Anbausatz Schaumdüse

For applying foam detergent in metered quantities in sanitary and food areas, or where long reaction time is necessary, mounts to spray lance in place of HP nozzle Order no. 2.637-926.0

# **Geka coupling**

Geka coupling with female thread Order no. 6.388-473.0

# Geka coupling

with hose liner Order no. 6.388-461.0

# Geka coupling

with hose liner Order no. 6.388-455.0

# **High pressure hoses**

# **High-pressure hose**

Food industry version, AVS connection in trigger gun grey ID 6/155 °C/230 bar Order no. 6.390-445.0





Ø

Ø

ø







<b>High-pressure hose</b> With patented AVS connection in trigger gun (pivot mounted ) and hand screw union. M22x1.5 with anti-kink protection ID 6/155°C/250 bar Order no. 6.390-174.0	
<b>High-pressure hose 20 m, DN 8, PN 200 bar</b> With M 22x1.5 union at both ends and anti-kink protection ID 8/155°C/315 bar Order no. 6.390-031.0	
	ø
<b>High-pressure hose 20 m, DN 10, PN 400 bar, Longlife, extension</b> Longlife 400, With rotary coupling 2 x M22 x 1.5, ID 8/155°C/400 bar Order no. 6.390-027.0	
<b>High-pressure hose 10 m, DN 10, PN 400 bar, Longlife, extension</b> Longlife 400, Without rotary coupling 2 x M22 x 1.5, ID 8/155°C/400 bar Order no. 6.390-026.0	
<b>High-pressure hose</b> With M 22x1.5 union at both ends and anti-kink protection ID 10/155 °C/220 bar	
Order no. 6.390-023.0	ø
<b>High-pressure hose, 15 m, DN 8, 315 bar, extension</b> With M 22x1.5 union at both ends and anti-kink protection ID 8/155 °C/315 bar Order no. 6.390-010.0	
	Ţ.
<b>High-pressure hose 10 m, DN 8, PN 315 bar, extension</b> With M 22x1.5 union at both ends and anti-kink protection ID 8/155°C/315 bar Order no. 6.389-891.0	
	ø
<b>High-pressure hose</b> With patented AVS connection in trigger gun (pivot mounted ) and hand screw union. M22x1.5 with anti-kink protection ID 6/155°C/250 bar Order no. 6.389-853.0	

Order no. 6.389-581.0

## **High-pressure hose, 20 m, DN 8, PN 180 bar, food version, extension** Food industry version with M 22x1.5 union at both ends, anti-kink protection, ID 8, with rotary coupling, for food industry, up to 230 bar

High-pressure hose, 10 m, DN 8, extension, food version

Food industry version with M 22x1.5 union at both ends, anti-kink protection, ID 8, with rotary coupling, for food industry, up to 230 bar Order no. 6.389-479.0

**High-pressure hose, 10 m, DN 8, incl. swivelling joint** Longlife 400, With rotary coupling 2 x M22 x 1.5, ID 8/155°C/400 bar Order no. 6.388-083.0

# HP detergent injector

# HP detergent injector

Adds up to 5% detergent in high-pressure mode Order no. 3.637-170.0

# Inno Foam Set

## Inno Foam Set

Complete, ready-to-use HP foam system for use with mobile and stationary HD/HDS units for cleaning and disinfection. Twin spray lance with foam nozzle and changeover to HP jet for clear rinsing etc., HP chemical injector with precision 0-5% metering valve. Order no. 2.640-151.0

# **Installationsmaterial**

# Rotating joint

Reliably prvents HP hose twisting. M 22x1.5 connection with protector Order no. 4.401-076.0













# © 2007 Alfred Kärcher GmbH & Co. KG

# Cold water middle class HD 7/18-4 MX Plus

# Kugeldüsenträger

## Rollover nozzle holder

Changes from solid to fan jet with flick of the wrist. Knurled nut for changeover to low pressure chemical intake, without nozzles (order Kärcher Power nozzle separately) Order no. 4.764-012.0

## Kupplung

**Double pipe union** For connecting and extending HP hoses. 2 x M22 x 1,5 connections, brass with rubber protector Order no. 4.403-002.0

# Machine-specific nozzle kit

Machine-specific nozzle kit detergent injector + HP nozzle + union Order no. 4.769-045.0

## Power nozzle with union

for item 2.838-821 and 2.640-355 Order no. 2.640-401.0

## Nozzle kits for Inno/Easy Set

## Nozzle kits for Inno/Easy Set

Ideally match performance to different machine outputs for economic operation. Order no. 2.640-687.0













# Nozzle pack for wet-blasting attachment Nozzle pack for wet-blasting attachment Consisting of wet-blasting nozzle and nozzle insert, only for use with wetblasting attachment 4762-010/-022 Order no. 2.637-900.0

# Pipe cleaning hose, ID 6

<b>Pipe cleaning hose ID 6</b> Very flexible high-pressure hose Order no. 6.390-030.0	e for pipe cleaning (1/8"connection for nozzle)	
		Ţ.
<b>Pipe cleaning hose, ID 6</b> Very flexible high-pressure hose Order no. 6.390-029.0	e for pipe cleaning (1/8"connection for nozzle)	
		ø
<b>Pipe cleaning hose, ID 6</b> Very flexible high-pressure hose Order no. 6.390-028.0	e for pipe cleaning (1/8"connection for nozzle)	

**Pipe cleaning nozzle** 

<b>Pipe cleaning nozzle</b> With female thread, different spraying directions for environment-friendly cleaning of blocked drains and pipes.Nozzle orifices are positioned so that nozzle pulls itself and the hose into the pipe 4 rotating jets Order no. 6.415-428.0	ø
<b>Pipe cleaning nozzle</b> With female thread, different spraying directions for environment-friendly cleaning of blocked drains and pipes. Nozzle orifices are positioned so that nozzle pulls itself and the hose into the pipe. $3 \times 30$ °backwards, $\in 16$ mm Order no. 5.763-019.0	ø



Ø

Ø

ø

Ø

# Cold water middle class HD 7/18-4 MX Plus

### Pipe cleaning nozzle

With female thread, different spraying directions for environment-friendly cleaning of blocked drains and pipes. Nozzle orifices are positioned so that nozzle pulls itself and the hose into the pipe. 1x forwards, 3x30° backwards, € 30 mm Order no. 5.763-017.0

### Pipe cleaning nozzle

With female thread, different spraying directions for environment-friendly cleaning of blocked drains and pipes. Nozzle orifices are positioned so that nozzle pulls itself and the hose into the pipe. 1x forwards, 3x30° backwards, € 16 mm Order no. 5.763-016.0

## Pipe cleaning nozzle

With female thread, different spraying directions for environment-friendly cleaning of blocked drains and pipes. Nozzle orifices are positioned so that nozzle pulls itself and the hose into the pipe.  $3 \times 30$  °backwards,  $\in$  16 mm Order no. 5.763-015.0

## **Pivoting spray lancer**

### **Pivoting spray lancer**

Spray lances in various lenghts, stainless steel with hand screw union. Ergonomically shaped handle mouldings for optimum control and insulaton. Can be turned 360° under pressure. Order no. 4.760-550.0

### Spray lance, 2040 mm, rotatable

Spray lances in various lenghts, stainless steel with hand screw union. Ergonomically shaped handle mouldings for optimum control and insulaton. Can be turned 360° under pressure. Order no. 4.760-366.0

### Spray lance, 1500 mm, rotatable

Spray lances in various lenghts, stainless steel with hand screw union. Ergonomically shaped handle mouldings for optimum control and insulaton. Can be turned 360° under pressure. Order no. 4.760-365.0

## **Pivoting spray lance**

Spray lances in various lenghts, stainless steel with hand screw union. Ergonomically shaped handle mouldings for optimum control and insulaton. Can be turned 360° under pressure. Order no. 4.760-364.0

### **Pivoting spray lancer**

Spray lances in various lenghts, stainless steel with hand screw union. Ergonomically shaped handle mouldings for optimum control and insulaton. Can be turned 360° under pressure. Order no. 4.760-386.0

## Push-on washing brush

Push-on washing brush

Order no. 4.762-324.0

## Rotary washing brush

### Rotary washing brush

Driven by water jet. Gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 85 °C. M 18 x 1.5. (replaceable brush element) Order no. 4.762-288.0

### Rotary washing brush

Driven by water jet. Gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 85 °C. M 18 x 1.5. (replaceable brush element) Order no. 4.762-284.0













#### © 2007 Alfred Kärcher GmbH & Co. KG

# Cold water middle class HD 7/18-4 MX Plus

### Self-winding hose reel for wall mounting

#### Add-on kit wall fastening hose reel

Add- on kit to fasten a hose reel at the wall. Order no. 2.639-931.0

#### Hose reel without hp-hose, automatic

Self-winding hose reel (without HP hose) Kärcher HD hose plug-in system Order no. 2.639-919.0

## **Spray lance**

Spray lance, 250 mm, fixed Stainless steel with hand screw union, does not pivot In conjunction with extended trigger aun Order no. 4.760-058.0

### Suction filter

### Suction filter

With/without non-return valve, brass Order no. 4.730-019.0

#### Suction filter

With/without non-return valve, brass Order no. 4.730-012.0

## Unterbodenstrahlrohr

**Underbody lance** 

Mobile. For effective and convenient cleaning of underbodies and wheel arches. Stainless steel. Without HP nozzle Order no. 4.760-245.0

Ø











Ø





### Variable pressure spray lance

### Variable pressure spray lance

With integral pressure gauge for infinitely variable pressure control directly on lance. Nozzle connection M 24 x 1.5. Chemical feed in low pressure mode. Variable pressure lance and Kärcher Power nozzle. Order no. 4.760-362.0

### Variable pressure spray lance

With integral pressure gauge for infinitely variable pressure control directly on lance. Nozzle connection M 24 x 1.5. Chemical feed in low pressure mode. Variable pressure lance and Kärcher Power nozzle. Order no. 4.760-230.0

### Verbindungsstück

#### Adapter

For connecting HP nozzles and accessories directly to trigger gun ( with nozzle union) 1 x M22 x 1.5/ 1 x M18 x 1.5 Order no. 4.402-022.0

Water supply hose

Water supply hose ID 19 R1"/R 3/4" - up to 85°C - for suction mode Order no. 4.440-207.0

#### Water supply hose

ID13 R1"/R 3/4" - up to 30°C Order no. 4.440-038.0

## WC-Strahlrohr

### WC-Spray lance

With nozzle. Specially shaped for cleaning WCs. Stainless steel. Order no. 4.760-073.0

ø

Ø

Ø



### Wet blasting attachment

### Wet-blasting attachment (without nozzles)

Adds abrasive to high-pressure jet. For removing paint, rust, scale. Mounts to spray lance in place of HP nozzle. Without abrasive flow control Order no. 4.762-022.0

### Wet blasting attachment ( without nozzles)

Adds abrasive to high-pressure jet. For removing paint, rust, scale. Mounts to spray lance in place of HP nozzle. With abrasive flow control Order no. 4.762-010.0

