

Technical Specification: HD 830 BS 1.187-113

High-pressure nozzle (US-gpm at 40 psi)	Größe	040	size	040
High-pressure mode, handgun with new nozzle (testing pressure gauge)	bar	≥ 105	psi	1522
Flow rate, high-pressure	l/min	9,2	USgpm	2.39
High-pressure pump, oil quantity	Liter	0,2	fl.oz.	6.7
High-pressure pump, oil type	SAE	15 W 40	SAE	15 W 40
Water supply, pressure	bar	2 - 6	psi	29 - 87
Water supply, flow rate	l/min	11	USgpm	3
Water supply, temperature	oC	60	oF	140
Water supply, hose diameter	Zoll	3/4	in	3/4
Water supply, hose length	m	7,5	ft	24
Internal combustion engine HONDA	Typ	GC 160	type	GC 160
Internal combustion engine, operating speed	U/min.	3250-3400	rpm	3250-3400
Internal combustion engine, idle speed	U/min.	3500-3650	rpm	3500-3650
Internal combustion engine, oil quantity	Liter	0,56	fl.oz.	18.9
Internal combustion engine, oil type	SAE	10 W 30	SAE	10 W 30
Sound level	dB(A)	93,5	dB(A)	93.5

FKV: 0.091-996

Circuit diagram: - - -

Dated: 08.01 ber