

# RM 69 ASF

Basic floor cleaner

## PRODUCT INFORMATION

**Powerful cleaner for very stressed industrial floors  
- preferable processing with floor scrubbers -**

### Properties:

- \* intensive acting floor cleaner for floor scrubbers
- \* solves severe soilings with grease, oil, soot and minerals
- \* easily oil-/water splitting in the oil separator (ASF)
- \* free of phosphates
- \* pH-value approx. 12 in concentrate
- \* blue liquid with a characteristic fresh odour



### Fields of application:

- \* industrial floors
- \* floor cleaning
- \* supermarkets
- \* workshops
- \* vehicle trade

**Processing:** manual or with floor scrubber machines

	<b>concentration in the tank</b>	<b>temperature</b>
* maintenance cleaning	0.5-1%	up to 60°C
* basic cleaning	10-25%	up to 60°C

### Economy

for the application with floor- scrubber machines: at a 1% solution, 1 l is sufficient for the maintenance cleaning of approx. 950 m<sup>2</sup>.

### Handling:

at first put the water into the tank and then add cleaning agent and mix it; when using large machines, make the predilution separately and then put into the tank.

### Remarks:

- \* strong alkaline, therefore use only on alkali- unsensitive surfaces (we recommend pre-tests for material compatibility)
- \* do not allow to dry cleaning agent solutions on the surface.
- \* after basic cleaning wipe with clear water
- \* no application on wood or unsealed parquet

# **RM 69 ASF**

Basic floor cleaner

## PRODUCT INFORMATION

### **Attention:**

Xi Irritant; R 36/38 Irritating to eyes and skin.

R 43 May cause sensitization by skin contact

S 24 Avoid contact with skin

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 37/39 Wear suitable gloves and eye/face protection.

S 46 If swallowed, seek medical advice and show this container or label.

S 60 This material and its container must be disposed of as hazardous waste.

### **Further information:**

\* Material safety data sheet

### **Process:**

- \* adjusting the floor scrubber – fitting brushes/disc, squeegee stripes
- \* prepare the solution of cleaning agent – put it into the tank
- \* clean the object
- \* basic cleaning (10-25% cleaning agent), rinse with clear water
- maintenance cleaning (0.5-1% cleaning agent), rinsing not necessary
- \* possible application of care agents/coatings

### **Alternative:**

- \* manual maintenance cleaning and application of care agents