Market Launch



makes a difference

110				
Version	Part-Number	Available ex LZ		
Version HDS 5/13 U *EU	Part-Number 1.064-010	Available ex LZ week 36/2010		
HDS 5/13 U *EU HDS 5/13 UX *EU HDS 5/15 U *EU	1.064-010 1.064-011 1.064-021	week 36/2010 week 36/2010 week 36/2010		
HDS 5/13 U *EU HDS 5/13 UX *EU	1.064-010 1.064-011	week 36/2010 week 36/2010		

Yellow File HDS 5/13 U/UX Yellow File HDS 5/15 U/UX Data sheet HDS 5/13 U



makes a difference

HDS 5/13 U



Technical Data

Power supply	230 V /1 ~/ 50 Hz
Water flow rate	500 l/h
Pressure	125 bar / 12,5 MPa
 Consumption fuel oil 	3,1 kg/h
 Connected load 	2,6 kW
 Max. temperature 	3° 08
 Weight (without accessories) 	70 kg
 Bio-diesel, can be used without from 10°C upwards 	restriction

Customer Benefits

- Extremely mobile, manoeuvrable machine for alternating site of operation
- Large wheels and "Upright"-Design for easy transport over stairs/ stages etc.
- Space saving stowable in vehicles
- Integrated accessory storage for whole spraying device
- Ergonomic push/ pull handle
- Well-aranged, central control panel
- Big water fine mesh filter protects high pressure pump from dirt particles

Standard Accessories



High-pressure hose 10 m, ID 6,
 250 bar, AVS-connection



Extended trigger gun



Product Idea:

Price attractive hot water high pressure cleaner in the entry class for commercial target groups like craftsmen (sanitary, lock smith, painter, heating installer), small garages, small metal working companies etc.

Order No.: HDS 5/13 U *EU 1.064-010

Stainless steel spray lance, 550 mm



• Triple nozzle

Market Launch: KW 36/2010

Yellow File HDS 5/13 U/UX Yellow File HDS 5/15 U/UX Data sheet HDS 5/13 UX



makes a difference

HDS 5/13 UX



Technical Data

Power supply	230 V /1 ~/ 50 Hz
Water flow rate	500 l/h
Pressure	125 bar / 12,5 MPa
 Consumption fuel oil 	3,1 kg/h
 Connected load 	2,6 kW
 Max. temperature 	80 °C
 Weight (without accessories) 	72 kg
 Bio-diesel, can be used without 	restriction
from 10°C upwards	

Customer Benefits

- Extremely mobile, manoeuvrable machine for alternating site of operation
- Large wheels and "Upright"-Design for easy transport over stairs/ stages etc.
- Space saving stowable in vehicles
- Integrated accessory storage for whole spraying device
- Ergonomic push/ pull handle
- Well-aranged, central control panel
- Integrated hose-reel with 15 m high-pressure hose
- Big water fine mesh filter protects high pressure pump from dirt particles

Product Idea:

Price attractive hot water high pressure cleaner in the entry class for commercial target groups like craftsmen (sanitary, lock smith, painter, heating installer), small garages, small metal working companies etc.

Order No.: HDS 5/13 UX *EU 1.064-011

Standard Accessories



High-pressure hose 15 m, ID 6,
 250 bar, AVS-connection



Extended trigger gun



Stainless steel spray lance, 550 mm



• Triple nozzle

Market Launch: KW 36/2010

Yellow File HDS 5/13 U/UX Yellow File HDS 5/15 U/UX Data sheet HDS 5/15 U



makes a difference

HDS 5/15 U



Technical Data

Power supply	230 V /1 ~/ 50 Hz
Water flow rate	450 l/h
Pressure	150 bar / 15 MPa
Consumption fuel oil	2,7 kg/h
Connected load	2,7 kW
Max. temperature	0° 08
Weight (without accessories)	70 kg
Bio-diesel, can be used without re	estriction 🛛 📈
from 10°C upwards	

Customer Benefits

- Extremely mobile, manoeuvrable machine for alternating site of operation
- Large wheels and "Upright"-Design for easy transport over stairs/ stages etc.
- Space saving stowable in vehicles
- Integrated accessory storage for whole spraying device
- Ergonomic push/ pull handle
- Well-aranged, central control panel
- Big water fine mesh filter protects high pressure pump from dirt particles

Basic accessories



High-pressure hose 10 m, ID 6,
 250 bar, AVS-connection



Extended trigger gun



Product idea:

Price attractive hot water high pressure cleaner in the entry class for commercial target groups like craftsmen (sanitary, lock smith, painter, heating installer), small garages, small metal working companies etc.

Order No.: HDS 5/15 U *EU 1.064-021

Stainless steel spray lance, 550 mm



• Triple nozzle

Market Launch: KW 36/2010

PCH-stv-hp/V/PCM/Com./PCH/Produktinfo/Mobile HDS/Data sheet/.ppt

Yellow File HDS 5/13 U/UX Yellow File HDS 5/15 U/UX Data sheet HDS 5/15 UX



makes a difference

HDS 5/15 UX



Technical Data

Power supply	230 V /1 ~/ 50 Hz
Water flow rate	450 l/h
Pressure	150 bar / 15 MPa
 Consumption fuel oil 	2,7 kg/h
 Connected load 	2,7 kW
 Max. temperature 	0° 08
 Weight (without accessories) 	72 kg
 Bio-diesel, can be used without r from 10°C upwards 	restriction

Customer Benefits

- Extremely mobile, manoeuvrable machine for alternating site of operation
- Large wheels and "Upright"-Design for easy transport over stairs/ stages etc.
- Space saving stowable in vehicles
- Integrated accessory storage for whole spraying device
- Ergonomic push/ pull handle
- Well-aranged, central control panel
- Integrated hose-reel with 15 m high-pressure hose (UX-version)
- Big water fine mesh filter protects high pressure pump from dirt particles

Product idea:

Price attractive hot water high pressure cleaner in the entry class for commercial target groups like craftsmen (sanitary, lock smith, painter, heating installer), small garages, small metal working companies etc.

Order No.: HDS 5/15 UX *EU 1.064-021

Standard accessories



High-pressure hose 10 m, ID 6,
 250 bar, AVS-connection



Extended trigger gun



Stainless steel spray lance, 550 mm



• Triple nozzle

Market Launch: KW 36/2010