





Convenient, mobile, versatile: the HD 5/12 C cold water high-pressure cleaner for vertical and horizontal operation. With accessory storage, brass cylinder head and automatic pressure relief.



### 1 Mobility

- The integrated carrying handle on the front of the machine enables easy loading and convenient transport.
- Push handle can be retracted at the push of a button.



### 2 Flexibility

- Vertical and horizontal operation possible.
- The wheels are not on in horizontal operation. In this way, the machine offers maximum stability.



### 3 Accessory storage

- Screw connections (M 18 × 1.5) for storing surface cleaner directly on the machine.
- Practical nozzle compartments for triple nozzle and rotary nozzle.



### 4 Quality

- The automatic pressure relief protects the components and extends the service life.
- High-quality brass cylinder head.



## HD 5/12 C

- Automatic pressure relief
- For vertical and horizontal operation
- Easy Press spray gun and rotatable stainless steel spray lance

### Technical data

|                                     |                    |                 |
|-------------------------------------|--------------------|-----------------|
| <b>Order no.</b>                    | 1.520-120.0        |                 |
| <b>EAN code</b>                     | 4039784607446      |                 |
| <b>Supply voltage</b>               | <b>Ph / V / Hz</b> | 1 / 230 / 50    |
| <b>Flow rate</b>                    | <b>l/h</b>         | 500             |
| <b>Working pressure</b>             | <b>bar / MPa</b>   | 120 / 12        |
| <b>Max. pressure</b>                | <b>bar / MPa</b>   | 175 / 17.5      |
| <b>Max. water inlet temperature</b> | <b>°C</b>          | 60              |
| <b>Connection load</b>              | <b>kW</b>          | 2.5             |
| <b>Weight</b>                       | <b>kg</b>          | 23.7            |
| <b>Dimensions (L × W × H)</b>       | <b>mm</b>          | 380 × 360 × 930 |

### Equipment

|                                   |                        |                    |
|-----------------------------------|------------------------|--------------------|
| <b>Spray gun</b>                  | Easy Press trigger gun |                    |
| <b>Spray gun with soft grip</b>   | ■                      |                    |
| <b>High-pressure hose</b>         | <b>m</b>               | 10 / DN 6, 250 bar |
| <b>Spray lance</b>                | <b>mm</b>              | 850                |
| <b>Triple nozzle (0°/25°/40°)</b> | manual                 |                    |
| <b>Anti-twist system</b>          | ■                      |                    |
| <b>Pressure switch-off</b>        | ■                      |                    |
| <b>Servo Control</b>              | -                      |                    |

■ Included in delivery.

# Accessories for HD 5/12 C 1.520-120.0

**KÄRCHER**



|   |    | Order no.   | ID   | Max. working pressure | Length | Price | Description  |   |
|---|----|-------------|------|-----------------------|--------|-------|--|---|
| <b>Standard with unions on both sides</b>                                       |    |             |      |                       |        |       |  |   |
| High-pressure hose, 15 m, ID 8, 315 bar, including rotary coupling              | 1  | 6.390-010.0 | ID 8 | 315 bar               | 15 m   |       |  | ▲ |
| High-pressure hose, 20 m, ID 8, 315 bar, extension piece                        | 2  | 6.390-031.0 | ID 8 | 315 bar               | 20 m   |       |  | ▲ |
| High-pressure hose, 10 m, ID 8, 315 bar, extension piece                        | 3  | 6.391-342.0 | ID 8 | 315 bar               | 10 m   |       |  | ▲ |
| High-pressure hose, 30 m, ID 8, including rotary coupling                       | 4  | 6.390-293.0 | ID 8 | 315 bar               | 30 m   |       |  | ▲ |
| <b>Food industry version with unions on both sides</b>                          |    |             |      |                       |        |       |  |   |
| High-pressure hose, 10 m, DN 8, suitable for the food industry, extension piece | 5  | 6.389-479.0 | ID 8 | 250 bar               | 10 m   |       | 10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.                | ▲ |
| High-pressure hose, 20 m, ID 8, suitable for food industry, extension piece     | 6  | 6.389-581.0 | ID 8 | 250 bar               | 20 m   |       | 20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar. | ▲ |
| <b>Longlife 400 with unions on both sides</b>                                   |    |             |      |                       |        |       |  |   |
| High pressure hose ID 6, 10 m, including rotary coupling                        | 7  | 6.391-883.0 | ID 6 | 400 bar               | 10 m   |       | With rotary coupling, 2 x M 22 x 1,5   | ▲ |
| Longlife 400 high-pressure hose, 10 m, DN 8, extension piece                    | 8  | 6.391-354.0 | ID 8 | 400 bar               | 10 m   |       |  | ▲ |
| High-pressure hose Longlife 400, 15 m, ID 8, including rotary coupling          | 9  | 6.389-709.0 | ID 8 | 400 bar               | 15 m   |       | With rotary coupling, 2 x M 22 x 1.5   | ▲ |
| High-pressure hose Longlife 400, 30 m, ID 8, including rotary coupling          | 10 | 6.390-294.0 | ID 8 | 400 bar               | 30 m   |       |  | ▲ |
| High-pressure hose 1.5 m, ID 8, including connectors                            | 11 | 6.390-178.0 | ID 8 | 400 bar               | 1.5 m  |       | 1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).                            | □ |
| <b>Longlife food design with screw connections at both ends</b>                 |    |             |      |                       |        |       |  |   |
| High pressure hose food ID 8, 10 m  | 12 | 6.391-864.0 | ID 8 | 400 bar               | 10 m   |       | Longlife HP hose for use in the food industry. Außendecke##  | ▲ |
| High-pressure hose food industry 400 bar, 20 m, ID 8, including rotary coupling | 13 | 6.391-887.0 | ID 8 | 400 bar               | 20 m   |       | animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5  | ▲ |
| <b>Standard</b>   |    |             |      |                       |        |       |  |   |
| High-pressure hose, 10 m, ID 6, AVS trigger gun connector                       | 14 | 6.391-238.0 | ID 6 | 250 bar               | 10 m   |       | 10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.                             | ■ |
| High-pressure hose, 15 m, ID 6, AVS gun connection                              | 15 | 6.391-394.0 | ID 6 | 250 bar               | 15 m   |       |  | □ |
| High-pressure hose, 10 m, ID 8, AVS trigger gun connector                       | 16 | 6.390-025.0 | ID 8 | 315 bar               | 10 m   |       | 10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.                             | □ |
| High-pressure hose, 15 m, ID 8, AVS trigger gun connector                       | 17 | 6.390-185.0 | ID 8 | 315 bar               | 15 m   |       | 15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.                             | □ |
| High-pressure hose, 20 m, ID 8, AVS trigger gun connector                       | 18 | 6.390-171.0 | ID 8 | 315 bar               | 20 m   |       | 20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.                             | □ |
| High-pressure hose, 10 m, ID 6, 300 bar, AVS trigger gun connection             | 19 | 6.391-875.0 | ID 6 | 300 bar               | 10 m   |       | With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar   | □ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



|   | Order no. | ID          | Max. working pressure | Length  | Price | Description   |                          |
|---|-----------|-------------|-----------------------|---------|-------|---|--------------------------|
| <b>Longlife 400</b>   |           |             |                       |         |       |   |                          |
| High-pressure hose Longlife 400, 20 m, DN 8, AVS trigger gun connector                      | 20        | 6.390-208.0 | ID 8                  | 400 bar | 20 m  | 20 m high-pressure hose Longlife 400 (DN 8) with patented (rotating) AVS trigger gun connector and manual coupling. Two layer high-strength steel wire reinforced.            | <input type="checkbox"/> |
| Longlife 400 high-pressure hose, 10 m, DN 6, M 22 x 1.5                                     | 21        | 6.391-882.0 | ID 6                  | 400 bar | 10 m  | With patented AVS connection in the trigger gun (pivot-mounted).  | <input type="checkbox"/> |
| Longlife 400 high-pressure hose, 10 m, DN 8,  | 22        | 6.391-351.0 | ID 8                  | 400 bar | 10 m  |   | <input type="checkbox"/> |
| <b>Food industry version</b>  |           |             |                       |         |       |   |                          |
| High-pressure hose, 10 m, DN 8, AVS trigger gun connection, food, grey                      | 23        | 6.390-704.0 | ID 8                  | 250 bar | 10 m  | Food industry version, AVS connection in the trigger gun. grey NW 8/155 °C/250 bar  | <input type="checkbox"/> |
| High-pressure hose, 20 m, ID 8, AVS trigger gun connector, suitable for food industry, grey | 24        | 6.390-705.0 | ID 8                  | 250 bar | 20 m  | 20 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. NW 8/155 °C/250 bar.            | <input type="checkbox"/> |
| <b>Longlife food design</b>   |           |             |                       |         |       |   |                          |
| High-pressure hose Longlife 400, 10 m, ID 8, AVS trigger gun connection                     | 25        | 6.391-885.0 | ID 8                  | 400 bar | 10 m  | Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted) | <input type="checkbox"/> |
| High-pressure hose Longlife 400, 20 m, ID 8, AVS trigger gun connection                     | 26        | 6.391-886.0 | ID 8                  | 400 bar | 20 m  |   | <input type="checkbox"/> |
| <b>Special hoses</b>  |           |             |                       |         |       |   |                          |
| High-pressure hose 1.5 m, ID 8, including connectors, outlet bend                           | 27        | 6.388-886.0 | ID 8                  | 400 bar | 1.5 m |   | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



|   |   | Order no.   | Flow rate |  |  |  | Price | Description  |   |
|---|---|-------------|-----------|--|--|--|-------|--|---|
| <b>Easy Press high-pressure trigger gun with holding force reduction (Kärcher patent)</b> |   |             |           |  |  |  |       |  |   |
| Easy Press HP trigger gun with soft grip  | 1 | 4.775-463.0 |           |  |  |  |       | Easy press high-pressure trigger gun with softgrip. For high-pressure hoses DN 6 and DN 8 with 11 mm swivel diameter.  | ■ |
| <b>Trigger guns</b>   |   |             |           |  |  |  |       |  |   |
| High-end HP trigger gun   | 2 | 4.775-823.0 |           |  |  |  |       |  | □ |
| <b>Quick connect</b>  |   |             |           |  |  |  |       |  |   |
| Quick coupling  | 3 | 6.401-458.0 |           |  |  |  |       | For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1,5 female. | □ |
| Male coupling   | 4 | 6.401-459.0 |           |  |  |  |       | Hardened stainless steel nipple for quick coupling 6.401-458. With M22 x 1,5 male.   | □ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.


# Accessories for HD 5/12 C 1.520-120.0



|                                 |   | Order no.   | Max. working pressure | Nozzle size |  | Price | Description   |   |
|---------------------------------|---|-------------|-----------------------|-------------|--|-------|---|---|
| <b>Triple nozzles</b>           |   |             |                       |             |  |       |   |   |
| Triple nozzle 035               | 1 | 4.767-212.0 | 300 bar               | 35          |  |       | Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.     | ■ |
| <b>Dirt Blaster, small</b>      |   |             |                       |             |  |       |   |   |
| Dirt blaster                    | 2 | 4.767-022.0 | 180 bar               | 35          |  |       | Small rotary nozzle for dirt blaster. The rotating point jet achieves 10 times the cleaning performance. Outstanding working time thanks to ceramic nozzle and bearing ring. Max. 180 bar/18 MPa, 60°C. | □ |
| Dirt blaster - more Performance | 3 | 4.767-230.0 | 180 bar               | 35          |  |       | The new performance dirt blaster (nozzle size 035) with rotating point jet makes a big difference: up to 50% higher cleaning and area performance than its predecessor.                                 | □ |
| <b>Dirt blaster, large</b>      |   |             |                       |             |  |       |   |   |
| Dirt blaster                    | 4 | 4.763-931.0 | 300 bar               | 35          |  |       | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.               | □ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



|  |    | Order no.   | Max. working pressure | Length  |  | Price | Description  |   |
|--|----|-------------|-----------------------|---------|--|-------|--|---|
| <b>Rotating spray lances</b>             |    |             |                       |         |  |       |  |   |
| 850 mm spray pipe, rotatable             | 1  | 4.760-663.0 | 300 bar               | 850 mm  |  |       | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  | ■ |
| 600 mm spray pipe, rotatable             | 2  | 4.760-664.0 | 300 bar               | 600 mm  |  |       | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  | □ |
| 1050 mm spray pipe, rotatable            | 3  | 4.760-660.0 | 300 bar               | 1050 mm |  |       | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.   | □ |
| 1550 mm spray pipe, rotatable            | 4  | 4.760-661.0 | 300 bar               | 1550 mm |  |       | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.   | □ |
| 2050 mm spray pipe, rotatable            | 5  | 4.760-662.0 | 300 bar               | 2050 mm |  |       | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.   | □ |
| <b>Spray lances</b>                      |    |             |                       |         |  |       |  |   |
| Vibrasoft lance                          | 6  | 6.415-951.0 | 250 bar               | 950 mm  |  |       | The spring-loaded 360° loop handle significantly reduces the vibrations on the spray lance, reducing the physical burden on the user, e.g. when working with the dirt blaster. | □ |
| <b>Angular spray lance</b>               |    |             |                       |         |  |       |  |   |
| Spray lance for toilets and rain gutters | 7  | 4.760-073.0 |                       |         |  |       | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.   | □ |
| <b>Undercarriage spray lance</b>         |    |             |                       |         |  |       |  |   |
| Underbody lance                          | 8  | 4.760-245.0 |                       | 700 mm  |  |       | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.  | □ |
| <b>Spray lance</b>                       |    |             |                       |         |  |       |  |   |
| 250 mm lance, non-rotatable              | 9  | 4.760-667.0 |                       | 250 mm  |  |       | 250 mm stainless steel lance. With manual coupling. Non-rotatable.   | □ |
| <b>Double lance</b>                      |    |             |                       |         |  |       |  |   |
| Double lance 960 mm                      | 10 | 6.394-665.0 | 310 bar               | 960 mm  |  |       | 960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).                                  | □ |
| <b>Gutter cleaner</b>                    |    |             |                       |         |  |       |  |   |
| Gutter cleaning lance                    | 11 | 2.642-305.0 |                       |         |  |       | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.      | □ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



|  |   | Order no.   | Flow rate   | Nozzle size | Diameter | Price | Description  |                          |
|--|---|-------------|-------------|-------------|----------|-------|--|--------------------------|
| <b>FR Classic surface cleaner</b>                  |   |             |             |             |          |       |  |                          |
| FR Classic surface cleaner                         | 1 | 2.643-476.0 |             |             |          |       | The ideal entry-level model in the Kärcher surface cleaner range for cleaning surfaces indoors and outdoors. With splash guard and up to 150 bar working pressure.                       | <input type="checkbox"/> |
| <b>Hard surface cleaner FRV 30</b>                 |   |             |             |             |          |       |  |                          |
| FRV 30 surface cleaner                             | 2 | 2.642-999.0 |             |             |          |       |  | <input type="checkbox"/> |
| <b>Hard surface cleaner FR 30</b>                  |   |             |             |             |          |       |  |                          |
| Hard surface cleaner FR 30                         | 3 | 2.642-997.0 |             |             | 300 mm   |       |  | <input type="checkbox"/> |
| <b>FR 30 Me surface cleaner</b>                    |   |             |             |             |          |       |  |                          |
| Hard surface cleaner FR 30 Me                      | 4 | 2.640-355.0 |             |             | 300 mm   |       | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. | <input type="checkbox"/> |
| <b>Machine-specific nozzle kits for FR</b>         |   |             |             |             |          |       |  |                          |
| Nozzle kit for surface cleaners                    | 5 | 2.640-401.0 | 500-650 l/h |             |          |       | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).   | <input type="checkbox"/> |
| <b>Machine-specific nozzle kits for FR Classic</b> |   |             |             |             |          |       |  |                          |
| Nozzle kit for FR Classic 034                      | 6 | 2.885-313.0 |             | 34          |          |       | Nozzle kit specifically for FR Classic surface cleaner.  | <input type="checkbox"/> |
| <b>FRV 30 Me surface cleaner</b>                   |   |             |             |             |          |       |  |                          |
| FRV 30 Me  | 7 | 2.642-911.0 |             |             |          |       |  | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.




# Accessories for HD 5/12 C 1.520-120.0



|   |   | Order no.   | Nozzle size |  |  |  | Price | Description |                          |
|---|---|-------------|-------------|--|--|--|-------|-------------|--------------------------|
| <b>Power nozzle spray angle 15°</b>         |   |             |             |  |  |  |       |             |                          |
| Power nozzle spray angle 15°                | 1 | 2.885-225.0 | 36          |  |  |  |       |             | <input type="checkbox"/> |
| <b>Power nozzle spray angle 25°</b>         |   |             |             |  |  |  |       |             |                          |
| Power nozzle spray angle 25°                | 2 | 2.885-255.0 | 35          |  |  |  |       |             | <input type="checkbox"/> |
| 25° power nozzle for cleaning agent suction | 3 | 2.884-521.0 | 250         |  |  |  |       |             | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



|                              |   | Order no.   |  |  |  |  | Price | Description  |                          |
|------------------------------|---|-------------|--|--|--|--|-------|--|--------------------------|
| <b>Coupling</b>              |   |             |  |  |  |  |       |  |                          |
| Coupling                     | 1 | 4.403-002.0 |  |  |  |  |       | Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.   | <input type="checkbox"/> |
| <b>Connector</b>             |   |             |  |  |  |  |       |  |                          |
| Nozzle screws / screw socket | 2 | 4.402-022.0 |  |  |  |  |       | Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5. | <input type="checkbox"/> |
| <b>Coupling parts</b>        |   |             |  |  |  |  |       |  |                          |
| Articulated joint            | 3 | 6.987-705.0 |  |  |  |  |       | This articulated joint with variable angle adjustment (up to an angle of 120°) is recommended for cleaning hard to reach areas. Fits directly on the spray lance.                            | <input type="checkbox"/> |
| <b>Adapters</b>              |   |             |  |  |  |  |       |  |                          |
| Adapter M 22 – Swivel        | 4 | 4.424-004.0 |  |  |  |  |       | M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.          | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



|   |   | Order no.   | Nozzle size |  |  |  | Price | Description  |                          |
|---|---|-------------|-------------|--|--|--|-------|--|--------------------------|
| <b>Wet blasting attachment (without nozzle)</b>                     |   |             |             |  |  |  |       |  |                          |
| Wet blasting attachment with flow control (without nozzles)         | 1 | 4.762-010.0 |             |  |  |  |       | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.  | <input type="checkbox"/> |
| Wet blasting attachment without flow control (nozzles not included) | 2 | 4.762-022.0 |             |  |  |  |       | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.                          | <input type="checkbox"/> |
| <b>Nozzle kits for wet jet unit</b>                                 |   |             |             |  |  |  |       |  |                          |
| Nozzle kit for wet jet unit 035                                     | 3 | 2.638-526.0 | 35          |  |  |  |       | Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



|  |   | Order no.   | Max. working pressure | Nozzle size | Diameter | Price | Description   |                          |
|--|---|-------------|-----------------------|-------------|----------|-------|---|--------------------------|
| <b>Pipe cleaning hose, ID 6</b>              |   |             |                       |             |          |       |   |                          |
| Pipe cleaning hose, DN 6, 20 m, max. 120 bar | 1 | 6.390-028.0 | 120 bar               |             |          |       | The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).  | <input type="checkbox"/> |
| Pipe cleaning hose, DN 6, 30 m, max. 120 bar | 2 | 6.390-029.0 | 120 bar               |             |          |       | 30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).  | <input type="checkbox"/> |
| Pipe cleaning hose, DN 6, 20 m, max. 250 bar | 3 | 6.390-030.0 | 250 bar               |             |          |       | The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).  | <input type="checkbox"/> |
| <b>Pipe cleaning nozzle</b>                  |   |             |                       |             |          |       |   |                          |
| Pipe cleaning dirt blaster D 25 / 040        | 4 | 6.415-944.0 |                       | 40          | 25 mm    |       | The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling. | <input type="checkbox"/> |
| Pipe cleaning dirt blaster D 30 / 040        | 5 | 6.415-946.0 |                       | 40          | 30 mm    |       |   | <input type="checkbox"/> |
| Pipe cleaning dirt blaster D 35 / 040        | 6 | 6.415-948.0 |                       | 40          | 35 mm    |       |   | <input type="checkbox"/> |
| Pipe cleaning nozzle                         | 7 | 5.763-015.0 |                       | 55          | 16 mm    |       | 16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.                                    | <input type="checkbox"/> |
|  | 8 | 5.763-017.0 |                       | 50          | 30 mm    |       | Pipe cleaning nozzle with inner thread. Different spray directions. The hose moves freely through the pipe. (R 1/8" connection, 3 x 30° backwards, diameter 30 mm.)           | <input type="checkbox"/> |
| Rotating pipe cleaning nozzle                | 9 | 6.415-428.0 |                       | 50          | 16 mm    |       | Pipe cleaning nozzle with four rotating jets and inner thread. Different spray directions. The hose moves freely through the pipe. With R 1/8" connection.                    | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



|  |   | Order no.   | Flow rate   |  |  |  | Price | Description  |                          |
|--|---|-------------|-------------|--|--|--|-------|--|--------------------------|
| <b>Inno Foam Kit</b>                           |   |             |             |  |  |  |       |  |                          |
| Inno Foam Set with detergent injector          | 1 | 2.640-151.0 |             |  |  |  |       | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.                                  | <input type="checkbox"/> |
| <b>Easy Foam Set</b>                           |   |             |             |  |  |  |       |  |                          |
| Easy Foam Set with RM injector                 | 2 | 2.640-691.0 |             |  |  |  |       | HP foam system for use with HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately. | <input type="checkbox"/> |
| <b>Nozzle kits for Inno/Easy Foam Set</b>      |   |             |             |  |  |  |       |  |                          |
| Nozzle kit 055 for Inno / Easy Set 500-600 l/h | 3 | 2.640-870.0 | 500-600 l/h |  |  |  |       | Optimal adaptation to different machine outputs for economic use.  | <input type="checkbox"/> |
| <b>Foam nozzle mounting kit</b>                |   |             |             |  |  |  |       |  |                          |
| Foam nozzle attachment kit                     | 4 | 2.637-926.0 |             |  |  |  |       | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.   | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.


# Accessories for HD 5/12 C 1.520-120.0



|  |   | Order no.   | Length |  |  |  | Price | Description   |                          |
|--|---|-------------|--------|--|--|--|-------|---|--------------------------|
| <b>Automatic, self-winding hose reels</b>                    |   |             |        |  |  |  |       |   |                          |
| Automatic hose reel, coated                                  | 1 | 2.639-919.0 | 20 m   |  |  |  |       | Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.  | <input type="checkbox"/> |
| Powder-coated swivel holder                                  | 2 | 2.639-931.0 |        |  |  |  |       | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel. | <input type="checkbox"/> |
| Automatic hose reel, stainless steel, includes swivel holder | 3 | 6.391-421.0 | 20 m   |  |  |  |       | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.  | <input type="checkbox"/> |
| Automatic hose reel, powder-coated steel / plastic           | 4 | 6.392-975.0 | 20 m   |  |  |  |       | Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.                           | <input type="checkbox"/> |
| Automatic stainless steel / synthetic material hose drum     | 5 | 6.392-965.0 | 20 m   |  |  |  |       | Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.                                | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



|  |   | Order no.   | Length | Diameter |  | Price | Description  |                          |
|--|---|-------------|--------|----------|--|-------|--|--------------------------|
| <b>Starting current limiter</b>          |   |             |        |          |  |       |  |                          |
| Starting current limiter                 | 1 | 2.637-495.0 |        |          |  |       | Reduces starting current in single-phase supply and protects line fuse.  | <input type="checkbox"/> |
| <b>Geka coupling</b>                     |   |             |        |          |  |       |  |                          |
| Geka connector with hose barb, R 3/4"    | 2 | 6.388-455.0 |        |          |  |       | with hose liner  | <input type="checkbox"/> |
| Geka connector with inner thread, R 3/4" | 3 | 6.388-473.0 |        |          |  |       | with female thread   | <input type="checkbox"/> |
| <b>Suction filter</b>                    |   |             |        |          |  |       |  |                          |
| Suction filter with check valve          | 4 | 4.730-012.0 |        |          |  |       | Brass suction filter suitable for ponds, storage tanks, etc. With check valve.   | <input type="checkbox"/> |
| <b>Water fine filter</b>                 |   |             |        |          |  |       |  |                          |
| Water fine filter, with adapter          | 5 | 4.730-102.0 |        |          |  |       | Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1". | <input type="checkbox"/> |
| <b>Water supply hose</b>                 |   |             |        |          |  |       |  |                          |
| Water supply hose                        | 6 | 4.440-038.0 | 7.5 m  |          |  |       | NW 13 R1" / R 3/4", up to 30 °C  | <input type="checkbox"/> |
| <b>Backflow check valve</b>              |   |             |        |          |  |       |  |                          |
| Backflow preventer                       | 7 | 2.641-374.0 |        |          |  |       | To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection      | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



|   |   | Order no.   | Flow rate   |  |  |  | Price | Description  |                          |
|---|---|-------------|-------------|--|--|--|-------|--|--------------------------|
| <b>Rotating washing brush</b>                                     |   |             |             |  |  |  |       |  |                          |
| Rotating wash brush for < 800 l/h machines, natural hair bristles | 1 | 4.762-560.0 | 500-800 l/h |  |  |  |       |  | <input type="checkbox"/> |
| Rotating wash brush for < 800 l/h machines, nylon bristles        | 2 | 4.762-561.0 | 500-800 l/h |  |  |  |       | The rotating wash brush gently removes fine dust and grime from all surfaces. Heat-resistant up to 80°C. (M 18 x 1.5, replaceable brush insert). | <input type="checkbox"/> |
| <b>Push-on washing brush</b>                                      |   |             |             |  |  |  |       |  |                          |
| Push-on wash brush  | 3 | 4.762-497.0 |             |  |  |  |       | The wash brush is fitted directly onto the devices' new dual and triple nozzles using clamping.  | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.