

Technical Specification:**HD 10/21 S *EU****1.286-320.0****Pre - version**

Supply voltage / Phase	V / PH	400 / 3	V / PH	400 / 3
Supply voltage, allowable tolerance	V	376 - 427	V	376 - 427
Frequency	Hz	50	Hz	50
Current consumption, high-pressure (after 4 min.)	A	< 13,5	A	< 13,5
Motor protective switch adjustment	A	14	A	14
Connecting load	kW	8	kW	8
High-pressure nozzle (US-gpm at 40 psi)	Größe	052	size	052
Overflow valve opening pressure (testing pressure gauge)	bar	185 - 191	psi	2683 - 2770
High-pressure mode, handgun with new nozzle (testing pressure gauge)	bar	170 - 185	psi	2465 - 2683
Flow rate, high-pressure	l/min	15,17 - 16,00	USgpm	3,9 - 4,16
Flow rate cleaning agent, high-pressure	l/min	> 0,67	USgpm	> 0,2
High-pressure pump, oil type	SAE	90	SAE	90
High-pressure pump, oil quantity	Liter	1,1	fl.oz.	37,18
Water supply, pressure	bar	10	psi	145
Water supply, flow rate	l/min	20	USgpm	5,2
Water supply, temperature	C	60	F	140
Water supply, hose diameter	Zoll	3/4	in	3/4
Water supply, hose length	m	7,5	ft	24,608

FKV: 0.091-966.0

Stromlaufplan: 0.088-605.0

Stand: 02/06 SRP

FKV: 0.091-966.0

Circuit diagram: 0.088-605.0

Date: 02/06 SRP