



		R 55 D 55	R 65 D 65	R 75 D 75	R 90 D 90	Standard, standard, standard	ölfest, oil resistant, resistant l'huile	Anti Streifen ölfest, anti stripes oil resistant, anti marques resistant l'huile	ölfest für struk- turierte Böden, oil resistant for textured floors. resistant l'huile pour les sols structurés					
BR 30/4 C	300 mm					--	--	--	--	4.777-320.0	--			
BR 40/10 C	435 mm					--	--	--	--	4.777-323.0	--			
BR/BD 40/25 C	770 mm					6.273-253.0	6.273-254.0	--	--	4.777-400.0	--			
BR/BD 45/40 C/W	850 mm					6.273-213.0	6.273-207.0	6.273-229.0	6.273-290.0	4.777-406.0	4.777-416.0			
BR/BD 55/40 C/W														
BR/BD 530														
B 60 W		x				--							4.777-401.0	4.777-411.0
B 90 R		x												
BR/BD 550														
B 95 RS										4.777-408.0				
BR 60/95 RS	910 mm					8.629-203.0	8.629-204.0	--	--	--	--			
BD 60/95 RS						8.629-201.0	8.629-202.0	--	--	--	8.602-517.0			
BR/BD 65/80 W	940 mm					--	6.273-208.0	6.273-205.0	6.273-291.0	4.777-402.0	4.777-412.0			
BR/BD 550 XL														
BR/BD Trike														
BR/BD 750														
BR/BD 55/60 W														
BR/BD 75/140 R														
B 60 W			x											
B 80 W				x	x *									
B 90 R				x	x									
B 140 R		x	x	x										
BR/BD 700	1060 mm					--	6.273-209.0	6.273-206.0	6.273-293.0	4.777-403.0	4.777-413.0			
BR/BD 90/140 R														
B 140 R					x									
BD 80/120	1130 mm					8.629-200.0	--	--	--	--	--			
BR/BD 100/250 R/RI	1180 mm					--	6.273-252.0	--	6.273-296.0	4.777-404.0	4.777-414.0			
BR/BD 120/250 R	1400 mm					--	6.273-210.0	6.273-216.0	6.273-295.0	4.777-405.0	4.777-415.0			
BR/BD 1000	1420 mm					--	6.273-210.0	6.273-216.0	6.273-295.0	4.777-051.0	4.777-057.0			

*) R 75